



ACR C-Strobe[™] & C-Strobe[™] H₂O



USCG+

SOLAS Approved The compact, rugged and waterproof C-Strobe and C-Strobe H_2O are USCG/SOLAS approved and have a 45 lumen LED that operates typically for 120 hours continuously in strobe mode.

ACR C-Strobe[™] & C-Strobe[™] H₂O

Manual/Water-Activated Emergency Signaling Lights

More About the C-Strobe™ series:

The new C-Strobe and C-Strobe H₂O personal distress strobe lights combine intense LED technology with increased operating life to provide you with the ultimate strobe distress lights. These personal distress strobe lights feature an impact resistant case – making them reliable, multi-purpose lights whenever efficient distress lighting is needed.

The C-Strobe is activated manually with an easy twist On/Off activation and the C-Strobe H_2O model includes two activation methods; the light can easily be activated with a simple push of the On/Off button or when in the armed position, can be activated automatically when immersed in water. The feature rich C-Strobe H_2O model also boasts 3 modes of operation; strobe, steady-on, and SOS.

The slim, lightweight and versatile design of these lights allows them to fit easily in a pocket or hang discreetly when attached to a life jacket or backpack. The flexible lashing loops on the side of the products allow for multiple mounting options including the webbing on your backpack or straps on your life jacket. hook and loop fastener strap can be secured around the lashing loops and creates

SPECIFICATIONS

C-Strobe C-Strobe H₂O 3965 (Bulk) / 3965.1 (Carded) 3964 (Bulk) / 3964.1 (Carded) **ACR Product Number** 5.06 x 1.38 x 1.2 inches (12.85 x 3.5 x 3.0 5.56 x 1.38 x 1.2 inches (14.1 x 3.5 x 3.0 Size cm) cm) 1.2 oz (33 g) 1.4 oz (40 g) Weight Manual Twist On/Off Manual On/Off Button or Water Activation Operation Activation Method Manual Activation Only Water or Manual Activation Tested for 24 hrs @ 3.3 ft (1m) Tested for 24 hrs @ 3.3 ft (1m) Waterproof 45 Lumen White LED 45 Lumen White LED Lamp USCG/SOLAS, CE, Transport Canada USCG/SOLAS, CE, Transport Canada Certification Light Type Strobe Strobe / Steady-On / SOS Minimum Performance (+ 0.75 >100 hr at -1 °C (strobe mode) >100 hr at -1 °C (Strobe Mode) CD) >120 hr at 30 °C (Strobe Mode) Typical Performance (+ 0.75 CD) >120 hr at 30 °C (strobe mode) Battery 2 AA Batteries 2 AA Batteries **Reverse Battery Protection** Yes Yes Accessories (with carded version) PFD Clip, Lanyard, hook and loop fastener PFD Clip, Lanyard, hook and loop fastener



d ed s ur

countless additional mounting possibilities. The lights also



USCG+ SOLAS Approved



LED Strobe Light



Fresh or Salt Water Activated (C-StrobeTM H_2O Only)



Manual Deactivation



120+ Hours

This document is the property of ACR Electronics, Inc. (ACR) and is distributed by ACR for the benefit of our customers. This document may not be disseminated, reproduced or altered in any way without the prior written approval of ACR Electronics, Inc.