



Product Bulletin

MODEL 9525A & 9525X
International

**20 Amp / 25 Amp Peak
Output Bench Charger /
Power Supply for
Standard Automotive,
Deep-Cycle, AGM and
Gel Cell batteries**



9525A



9525X

Specifications:

Model Number	9425A & 9425X
Electrical Requirements	240V-2A
Continuous Ratings	20A
Clamp Rating	300A
DC Leads	6.2' 10 AWG
Shipping Dimensions	12"x12"x14"
Weight	21 LBS
AC Cord / Voltage	6' 18-3
Battery Types	12 Volt Flooded, AGM, and Gel Cell batteries - including Spiral Cell, Orbital, or Optima batteries
Display	3 LED display indicating charge status

Features

- Micro-processor controlled and fully automatic charging of flooded batteries including GEL and AGM
- Analyzes battery condition and automatically selects proper charging technique
- Electrical Stability System (ESS™) technology feature is a stable power supply for extended service procedures or re-flashes, Nominal 13.9V DC output
- Model 9525A – AC Plug Continental Europe, Latin America & Middle East
- Model 9525X – AC Plug for China
- Program for deep discharge recovery of flooded batteries
- Patented diagnostics indicate weak or defective battery
- Utilizes three color LEDS to monitor charging status
- Switch for selecting battery type
- Dead Battery Override Control
- Maintains battery charge, can be left connected to battery

© 2016 Associated Equipment Corporation. All rights reserved. Because of ongoing product improvements, we reserve the right to change design, materials, and specifications without notice. Product shipped may differ from photo(s) shown.

Learn more about batteries and chargers we have.