

Collinite

No. 920 *Fiberglass Boat Cleaner*

-LIQUID MARINE CLEANER-



1. **Function:** Marine pre-wax cleaner for exterior vehicle finishes

- Removes surface contaminants caused by time and weathering
- Restores colors and enhances appearance
- Preps surface for follow-up application of Collinite's last step wax products; No. 845, 925, 476, 885, or 915.
- NOT a heavy-duty compound
- Contains mild cut cleaning agents/abrasives
- Has ability to remove previously applied layer(s) of wax to create uniform finish for next wax application

2. **Recommended for:**

- Tarnished/soiled/stained/discolored/weathered surfaces
- Fiberglass, gel coat, *light* colored clear coat paints (white, silver)
- Coated, non-coated and non-painted metals; aluminum, chrome, brass, copper, and stainless steel
- Marine, aeronautical/aircraft, and RV application

2a. **NOT for use on:**

- Dark clear coat paint or painted metals
- Surfaces unmentioned above, as testing has yet to be extensively conducted. Refer to Collinite directly with application inquiries.

3. **Directions for use:**

- Shake well before using
- Apply THIN amount of No. 920 to a small section no larger than 2X2 ft at a time
- Rub well to loosen all tarnish, oxidation etc. Reapply as necessary until surface is free of contaminants
- Immediately polish off with clean, dry soft cloth or microfiber towel

3a. **Application/Tech Tips:**

- Use in a well-ventilated area with protective eyewear and gloves
- Applicator pads and removal towels should be clean, free of residue
- Do NOT apply wax to sections larger than recommended before removing, as prolonged drying or cure times may lead to product hardening on surface; causing streaking or difficulty for some users to remove properly. User assumes risk if recommended cure times are exceeded.

Collinite

- Drying times may vary based on conditions (air and surface temperature, humidity, wind, sunlight etc).
- Avoid applying in extreme temperatures (over 80 degrees F or less than 55 degrees F). Surface temperatures should feel lukewarm-room temperature to the touch. Do not apply if surface feels cold or hot to the touch.
- Safe to use with machine buffer if experienced. Check machine manufacturer's speed/pad specifications for fiberglass cleaner that contain a mild-cut abrasive. NOT recommended for dark clear coats.
- For follow-up wax shine and protection (after No. 920 removal), apply one of Collinite's last step wax products; No. 845, 925, 476, 885, or 915.

4. Additional

- Store product at room temperature away from fire or flame
- Discard product if exposed to frozen temperatures
- Keep cap or lid on product when not in use
- Do not alter product's composition or original packaging in any way

5. Safety

See MSDS

6. Physical

Product consistency: milky/creamy liquid*

Sizes available: 16 fluid oz and 64 fluid oz (1/2 gal)