



Knock'er Loose® Penetrating Solvent, 13 Wt Oz

No. 03020 | Item# 1003270 | Case# 1003269

Product Description	An industrial strength, low viscosity super penetrant designed to quickly loosen and free seized, bound or frozen fasteners. Quickly permeates rust, scale, gum, grease and corrosion. Outperforms the competition as verified by independent tests.
Applications	Nuts and bolts, pins, screws, bushings, clips, hinges, snaps, lugs, caps, locks, washers and sliding mechanisms.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Penetrating Solvent
Net Fill	13 Wt Oz
UPC Code	078254030203
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.1H x 8.3W x 11.1D in
Cases Per Pallet	133
Case Weight	12 lbs
I 2 of 5 Code	30078254030204
Appearance	Reddish Liquid
Base Type	Petroleum
Flash point (F)	147°F
Flash point (C)	64°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.86
Plastic Safe	No
Film Type	Thin, Non-Drying
Evaporation Rate	Moderate
Dielectric Strength	35,200 Volts
Propellant	Carbon Dioxide
NSF Category Code	H2



NSF Number	132079
Aerosol Flammability Level	I
DOT Proper Shipping Name	Aerosols, Non-Flammable, Limited Quantity
VOC % (Consumer Product def)	23.6
VOC g/L (Consumer Product def)	203
VOC lbs/gal (Consumer Prod def)	1.7
VOC Category	Penetrant
Removal (How To)	Remove with Petroleum Distillates.



SAFETY DATA SHEET

1. Identification

Product identifier Knock'er Loose® Penetrating Solvent - 13 oz


Other means of identification
Product Code No. 03020 (Item# 1003270)

Recommended use Penetrant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information
Manufactured or sold by:

2. Hazard(s) identification

Physical hazards	Gases under pressure	Compressed gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1A
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		

Signal word

Danger

Hazard statement

Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49 °C/120 °F. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves. Avoid release to the environment.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Collect spillage.

Storage	Store locked up. Protect from sunlight. Store in a well-ventilated place. Exposure to high temperature may cause can to burst.
Disposal	Dispose of contents/container in accordance with local/regional/national regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated middle		64742-46-7	40 - 50
dipropylene glycol methyl ether acetate		88917-22-0	5 - 10
dipropylene glycol n-propyl ether		29911-27-1	5 - 10
turpentine, oil		8006-64-2	5 - 10
2,6-dimethyl-4-heptanone		108-83-8	3 - 5
fatty ester		Proprietary	3 - 5
carbon dioxide		124-38-9	1 - 3
distillates (petroleum), hydrotreated light		64742-47-8	1 - 3
naphtha (petroleum), hydrotreated heavy		64742-48-9	1 - 3
pine oil		8002-09-3	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
General fire hazards	Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
2,6-dimethyl-4-heptanone (CAS 108-83-8)	PEL	290 mg/m ³	
		50 ppm	
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m ³	
		5000 ppm	
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	PEL	5 mg/m ³	Mist.
turpentine, oil (CAS 8006-64-2)	PEL	560 mg/m ³	
		100 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2,6-dimethyl-4-heptanone (CAS 108-83-8)	TWA	25 ppm	
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m ³	Inhalable fraction.
turpentine, oil (CAS 8006-64-2)	TWA	20 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
2,6-dimethyl-4-heptanone (CAS 108-83-8)	TWA	150 mg/m ³	
carbon dioxide (CAS 124-38-9)	STEL	25 ppm	
		54000 mg/m ³	
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	30000 ppm	
		9000 mg/m ³	
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	5000 ppm	
		100 mg/m ³	Mist.
turpentine, oil (CAS 8006-64-2)	TWA	5 mg/m ³	Mist.
		560 mg/m ³	
		100 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin protection**Hand protection**

Wear protective gloves such as: Nitrile. Rubber.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties**Appearance****Physical state**

Liquid.

Form

Aerosol.

Color

Red.

Odor

Pleasant pine.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point	-121 °F (-85 °C) estimated
Initial boiling point and boiling range	300 °F (148.9 °C) estimated
Flash point	147 °F (63.9 °C) Setaf flash
Evaporation rate	Moderate.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.6 % estimated
Flammability limit - upper (%)	8.3 % estimated
Vapor pressure	1958.8 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.86
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	401 °F (205 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Percent volatile	96.4 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Chlorine.
Hazardous decomposition products	Aldehydes. Ketones. Organic acids. Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
---	---

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways.
-----------------------	---

Components	Species	Test Results
2,6-dimethyl-4-heptanone (CAS 108-83-8)		
Acute		
Dermal		
LD50	Rabbit	16200 mg/kg
Inhalation		
LC50	Rat	> 5 mg/l, 4 hours

Components	Species	Test Results
Oral LD50	Rat	5285 mg/kg
carbon dioxide (CAS 124-38-9)		
Acute Inhalation Gas LC50	Rat	470000 ppm, 30 minutes
dipropylene glycol n-propyl ether (CAS 29911-27-1)		
Acute Dermal LD50	Rabbit	> 2000 mg/kg 5340 mg/kg
Oral LD50	Rat	> 2000 mg/kg 1475 mg/kg
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
Acute Dermal LD50	Rat	> 2000 mg/kg
Inhalation LC50	Rat	> 5.2 mg/l, 4 hours
Oral LD50	Rat	> 5000 mg/kg, 2.5 hours
naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)		
Acute Dermal LD50	Rabbit	> 2000 mg/kg
Oral LD50	Rat	> 5000 mg/kg
turpentine, oil (CAS 8006-64-2)		
Acute Inhalation LC50	Rat	3590 mg/l, 1 Hours
Oral LD50	Rat	5760 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
ACGIH sensitization		
TURPENTINE AND SELECTED MONOTERPENES (CAS 8006-64-2)		Dermal sensitization
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)		
Not regulated.		

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test Results	
dipropylene glycol n-propyl ether (CAS 29911-27-1)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	> 100 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>)	> 100 mg/l, 96 hours
distillates (petroleum), hydrotreated light (CAS 64742-47-8)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	> 1000 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>)	> 1000 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

dipropylene glycol n-propyl ether

0.87 OECD 107
0.88 OECD 107

Mobility in soil No data available.

Other adverse effects Not available.

13. Disposal considerations

Disposal instructions The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty container can be recycled. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT



UN number	UN1950
UN proper shipping name	Aerosols, non-flammable, Limited Quantity
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, non-flammable, Limited Quantity
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Packing group	Not applicable.
ERG Code	2L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes, but exempt from the regulations.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG**IATA**

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.
SARA 304 Emergency release notification	Not regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)	Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4)	Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

2,6-dimethyl-4-heptanone (CAS 108-83-8)

Other Flavoring Substances with OSHA PEL's

Food and Drug Administration (FDA) Not regulated.**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

Classified hazard categories Gas under pressure
Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitization
Aspiration hazard

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes**SARA 313 (TRI reporting)**
Not regulated.**US state regulations****US. New Jersey Worker and Community Right-to-Know Act**

2,6-dimethyl-4-heptanone (CAS 108-83-8)
carbon dioxide (CAS 124-38-9)
pine oil (CAS 8002-09-3)
turpentine, oil (CAS 8006-64-2)

US. Massachusetts RTK - Substance List

2,6-dimethyl-4-heptanone (CAS 108-83-8)
carbon dioxide (CAS 124-38-9)
turpentine, oil (CAS 8006-64-2)

US. Pennsylvania Worker and Community Right-to-Know Law

2,6-dimethyl-4-heptanone (CAS 108-83-8)
carbon dioxide (CAS 124-38-9)
distillates (petroleum), hydrotreated light (CAS 64742-47-8)
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)
naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

US. Rhode Island RTK

2,6-dimethyl-4-heptanone (CAS 108-83-8)
carbon dioxide (CAS 124-38-9)
distillates (petroleum), hydrotreated light (CAS 64742-47-8)
distillates (petroleum), hydrotreated middle (CAS 64742-46-7)
turpentine, oil (CAS 8006-64-2)

California Proposition 65**WARNING:** Cancer and Reproductive Harm**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

benzene (CAS 71-43-2)	Listed: February 27, 1987
ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
naphthalene (CAS 91-20-3)	Listed: April 19, 2002

California Proposition 65 - CRT: Listed date/Developmental toxin

benzene (CAS 71-43-2)

Listed: December 26, 1997

toluene (CAS 108-88-3)

Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

benzene (CAS 71-43-2)

Listed: December 26, 1997

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Volatile organic compounds (VOC) regulations**EPA****VOC content (40 CFR 51.100(s))** 98.4 %**Consumer products (40 CFR 59, Subpt. C)** Not regulated**State****Consumer products** This product is regulated as a Penetrant. This product is compliant for use in all 50 states.**VOC content (CA)** 23.6 %**VOC content (OTC)** 23.6 %**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-01-2019
Prepared by	Allison Yoon
Version #	01
Further information	CRC # 548A/1002565

Disclaimer The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

Revision information This document has undergone significant changes and should be reviewed in its entirety.