



Class Cleaner

Polessional Strength Fisile Sale Strak Eliminating Formula Familia

WARNING: WE CAUSE EVE IRRITATION UNTENTS UNDER PRESSUR Ser ANAY FROM CHILDREN Ser WARNER SO BACK COOL

OVERTENCIA: PUEDE ASM ERTACIÓN OCULAR. OTRIOU BAJO PRESION. INITEIGA FUERA DEL SINE AMERICAS EN GLOSSO

NO. Net Wt./Pe HydroForce® Glass Cleaner, Professional Strength, 18 Wt Oz No. 14412 | Item# 1004966 | Case# 1004965

> Cuts through dirt, dust, fingerprints and haze deposits. Provides streak-free glass cleaning even on delicate glass

surfaces. Biodegradable, ready to use.

Product Description

Applications	Glass, mirrors
Unit Package Description	20 Ounce Aerosol
Generic Description 1	Glass Cleaner
Brand	CRC
Net Fill	18 Wt Oz
UPC Code	078254144122
Unit Dimensions	9.25H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	9.7H x 8.3W x 11.1D in
Cases Per Pallet	114
Case Weight	16 lbs
I 2 of 5 Code	30078254144123
Appearance	Clear Colorless Liquid
Base Type	Water Based
Flash point (F)	None
Flash point (C)	None
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.9952
рН	10.5
Plastic Safe	Yes
Evaporation Rate	Slow
Propellant	Hydrocarbon
NSF Category Code	C1
NSF Number	126580
Ford Tox No.	191378





Glass Cleaner Limplador de Vidrios

Professional Strength Pastic Sale Strak Eliminating Formula Isaming

Concentrado Profesional Incuo para el Plástico fomula de Eliminación de Vetas Esquina

WARNING

UVERTENCIA:



Aerosol Flammability Level I DOT Proper Shipping Name VOC % (Consumer Product def) VOC g/L (Consumer Product def) VOC lbs/gal (Consumer Prod def) VOC Category Removal (How To)

Aerosols, Non-Flammable, Limited Quantity 9.6 95.1

0.8

Glass Cleaners - Aerosol Remove with water.



SAFETY DATA SHEET

1. Identification

Product identifier	HydroForce® Glass Cleaner - 18 oz			
Other means of identification				
Product Code	No. 14412 (Item# 1004966)	No. 14412 (Item# 1004966)		
Recommended use	Glass cleaner			
Recommended restrictions	None known.			
2. Hazard(s) identificatio				
Physical hazards	Gases under pressure	Liquefied gas		
Health hazards	Not classified.			
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3		
	Hazardous to the aquatic environment, long-term hazard	Category 3		

OSHA defined hazards

Label elements



Not classified.

Signal word	Warning	
Hazard statement	Contains gas under pressure; may explode if heated. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.	
Precautionary statement		
Prevention	Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49 °C/120 °F. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use. Avoid release to the environment.	
Response	Wash hands after handling.	
Storage	Protect from sunlight. Store in a well-ventilated place. Exposure to high temperature may cause can to burst.	
Disposal	Dispose of contents/container in accordance with local/regional/national regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
water		7732-18-5	80 - 90
liquefied petroleum gas		68476-86-8	5 - 10
2-butoxyethanol		111-76-2	1 - 3
ethanol		64-17-5	1 - 3
ammonia		7664-41-7	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.		
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.		
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.		
Ingestion	Call a POISON CENTER or doctor/physician.		
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.		
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.		

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
General fire hazards	Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). This product is miscible in water. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	

Precautions for safe handling Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label. Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120 °F/49 °C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Lin Components		Туре			Value
2-butoxyethanol (CAS 111-76-2)		PEL			240 mg/m3
					50 ppm
ammonia (CAS 7664-41-	7)	PEL			35 mg/m3
					50 ppm
ethanol (CAS 64-17-5)		PEL			1900 mg/m3
					1000 ppm
US. ACGIH Threshold L	imit Values				
Components		Туре			Value
2-butoxyethanol (CAS 111-76-2)		TWA			20 ppm
ammonia (CAS 7664-41-	7)	STEL			35 ppm
		TWA			25 ppm
ethanol (CAS 64-17-5)		STEL			1000 ppm
US. NIOSH: Pocket Guid	de to Chemical Haz	ards			
Components		Туре			Value
2-butoxyethanol (CAS 111-76-2)		TWA			24 mg/m3
					5 ppm
ammonia (CAS 7664-41-	7)	STEL			27 mg/m3
					35 ppm
		TWA			18 mg/m3
					25 ppm
ethanol (CAS 64-17-5)		TWA			1900 mg/m3
					1000 ppm
ogical limit values					
ACGIH Biological Expo	sure Indices				
Components	Value		Determinant	Specimen	Sampling Time
2-butoxyethanol (CAS	200 mg/g		Butoxyacetic	Creatinine	in *

* - For sampling details, please see the source document.

Exposure guidelines

111-76-2)

US - California OELs: Skin designation	
2-butoxyethanol (CAS 111-76-2)	Can be absorbed through the skin.
US - Minnesota Haz Subs: Skin designation applies	
2-butoxyethanol (CAS 111-76-2)	Skin designation applies.
US - Tennessee OELs: Skin designation	
2-butoxyethanol (CAS 111-76-2)	Can be absorbed through the skin.
US NIOSH Pocket Guide to Chemical Hazards: Skin d	esignation
2-butoxyethanol (CAS 111-76-2)	Can be absorbed through the skin.

acid (BAA),

with hydrolysis

urine

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-butoxyethanol (CAS 1	11-76-2) Can be absorbed through the skin.	
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
Individual protection measures	s, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).	
Skin protection		
Hand protection	Wear protective gloves such as: Nitrile. Rubber.	
Other	Wear suitable protective clothing.	
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	

9. Physical and chemical properties

,			
Appearance			
Physical state	Liquid.		
Form	Aerosol.		
Color	Clear.		
Odor	Ammoniacal.		
Odor threshold	Not available.		
рН	10.5		
Melting point/freezing point	Not available.		
Initial boiling point and boiling range	212 °F (100 °C) estimated		
Flash point	None.		
Evaporation rate	Slow.		
Flammability (solid, gas)	Not available.		
Upper/lower flammability or exp	losive limits		
Flammability limit - lower (%)	1.3 % estimated		
Flammability limit - upper (%)	25 % estimated		
Vapor pressure	280.3 hPa estimated		
Vapor density	> 1 (air = 1)		
Relative density	0.97 estimated		
Solubility(ies)			
Solubility (water)	Soluble.		
Partition coefficient (n-octanol/water)	Not available.		
Auto-ignition temperature	446 °F (230 °C) estimated		
Decomposition temperature	Not available.		
Viscosity	Not available.		
Percent volatile	99.6 % estimated		
10. Stability and reactivity	/		
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.		
Chemical stability	Material is stable under normal conditions.		

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.			
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.			
Incompatible materials	Strong oxidizing agents.			
Hazardous decomposition products	Carbon oxides. Aldehydes. Ketones. Organic acids.			
11. Toxicological inform	nation			
Information on likely routes of	f exposure			
Inhalation	Prolonged inhalation may be harr	Prolonged inhalation may be harmful.		
Skin contact	2-Butoxy ethanol may be absorbe prolonged. These effects have no	ed through the skin in toxic amounts if contact is repeated and ot been observed in humans.		
Eye contact	Direct contact with eyes may cau	se temporary irritation.		
Ingestion	Expected to be a low ingestion ha	azard.		
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cau	Direct contact with eyes may cause temporary irritation.		
Information on toxicological e	effects			
Acute toxicity	Not known.			
Components	Species	Test Results		
2-butoxyethanol (CAS 111-76-2 <u>Acute</u> Dermal)			
LD50 Oral	Rabbit	220 mg/kg		
LD50	Rat	470 mg/kg		
ammonia (CAS 7664-41-7)				
Acute Inhalation LC50	Rat	2000 ppm, 4 Hours		
Oral LD50	Rat	350 mg/kg		
ethanol (CAS 64-17-5)				
<u>Acute</u> Dermal				
LD50	Rabbit	20 g/kg		
Inhalation				
LC50	Rat	8000 mg/l, 4 hours		
Oral				
LD50	Rat	6200 mg/kg		
		6.2 g/kg		
	y be based on additional component d			
Skin corrosion/irritation	Prolonged skin contact may caus			
Serious eye damage/eye irritation	Direct contact with eyes may cau	se temporary irritation.		
Respiratory or skin sensitizati				
Respiratory sensitization	Not a respiratory sensitizer.	Not a respiratory sensitizer.		
Skin sensitization		This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	mutagenic or genotoxic.	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Construction	Net elegativelle as to estraine generative to humans			

IARC Monographs. Overall	Evaluation of Carcinogenicity
2-butoxyethanol (CAS 11	1-76-2) 3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulate	d Substances (29 CFR 1910.1001-1052)
Not regulated.	
US. National Toxicology Pro	ogram (NTP) Report on Carcinogens
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not classified.
Chronic effects	May be harmful if absorbed through skin. Prolonged inhalation may be harmful.
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

12. Ecological information

otoxicity Harmful		o aquatic life with long lasting effects.		
Components		Species	Test Results	
2-butoxyethanol (CAS	111-76-2)			
Aquatic				
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours	
ammonia (CAS 7664-4	11-7)			
Aquatic				
Fish	LC50	Chinook salmon (Oncorhynchus tshawytscha)	0.43 - 0.47 mg/l, 96 hours	
ethanol (CAS 64-17-5))			
Aquatic				
Acute				
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	5012 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	> 10000 mg/l, 96 hours	

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octan	bl / water (log Kow)	
2-butoxyethanol	0.83	
ethanol	-0.31	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty container can be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.
Hazardous waste code	Not regulated.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, non-flammable, Limited Quantity
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols, non-flammable, Limited Quantity
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Packing group	Not applicable.
ERG Code	2L
	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.



15. Regulatory information

US federal regulations	This produc		U.S. EPA TSCA Invent us Chemical" as defined 00.	ory List. d by the OSHA Hazard	Communication
TSCA Section 12(b) Ex	port Notificati	on (40 CFR 70	7, Subpt. D)		
Not regulated. SARA 304 Emergency	release notific	ation			
Not regulated.					
OSHA Specifically Reg Not regulated.	ulated Substa	inces (29 CFR	1910.1001-1052)		
US EPCRA (SARA Title	e III) Section 3 [,]	13 - Toxic Che	mical: Listed substan	ce	
2-butoxyethanol (CA CERCLA Hazardous Su	,	(40 CFR 302.4))		
2-butoxyethanol (CA	,				
CERCLA Hazardous Su Not listed.	ubstances: Re	portable quan	tity		
Spills or releases resultin Response Center (800-4					tion to the National
Other federal regulations					
Clean Air Act (CAA) Sectio	n 112 Hazardo	ous Air Polluta	nts (HAPs) List		
Not regulated. Clean Air Act (CAA) Section	n 112(r) Accid	ental Release	Prevention (40 CFR 6	8.130)	
Not regulated.					
Safe Drinking Water Act (SDWA)	Not regulate	ed.			
FEMA Priority Substan	ces Respirato	ory Health and	Safety in the Flavor N	anufacturing Workpla	ace
ethanol (CAS 64-17	-5)		Low priority		
Food and Drug Administration (FDA)	Not regulate	ed.			
Superfund Amendments and R	eauthorization	n Act of 1986 (S	SARA)		
Classified hazard categories	Gas under p	pressure			
SARA 302 Extremely hazar	dous substan	се			
Chemical name CA	AS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
ammonia 76	64-41-7	100	500		
SARA 311/312 Hazardous chemical	Yes				
SARA 313 (TRI reporting)					
Chemical name		C	AS number	% by wt.	
2-butoxyethanol			11-76-2	1 - 3	
ammonia		1	'664-41-7	< 1	
US state regulations			• /		
US. New Jersey Worker and		Right-to-Know	Act		
2-butoxyethanol (CAS 1 ammonia (CAS 7664-41 ethanol (CAS 64-17-5)	,				
US. Massachusetts RTK - S	Substance List	t			
2-butoxyethanol (CAS 1 ammonia (CAS 7664-41					
ethanol (CAS 64-17-5)					
US. Pennsylvania Worker a		y Right-to-Kno	ow Law		
2-butoxyethanol (CAS 1 ammonia (CAS 7664-41					
othanal (CAR RA 17 E)	-7)				
ethanol (CAS 64-17-5)	-7)				SDS US

US. Rhode Island RTK

ammonia (CAS 7664-41-7) ethanol (CAS 64-17-5)

California Proposition 65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

	•				
Cali	fornia Proposition 6	65 - CRT: Listed date/Ca	arcinogenic substance		
	methyl isobutyl ketone (CAS 108-10-1) Listed: November 4, 2011				
Cali	-	65 - CRT: Listed date/De	evelopmental toxin		
	methanol (CAS 67-56-1) Listed: March 16, 2012 methyl isobutyl ketone (CAS 108-10-1) Listed: March 28, 2014				
US.			Listed: March 28, 2014 r Consumer Products Regulations (Cal. Co	ode Reas, tit. 22, 69502.3.	
	d. (a))			, , , , , , , , , , , , , , , , , , ,	
	2-butoxyethanol (CA				
	ammonia (CAS 7664				
		gas (CAS 68476-86-8)			
Volatile orga EPA	anic compounds (VC	DC) regulations			
	C content (40 CFR	9.6 %			
51.1	l00(s))				
	sumer products CFR 59, Subpt. C)	Compliant			
State					
Con	sumer products	This product is regulated as a Glass Cleaner (aerosol). This product is compliant for use in all 50 states.			
VOO	C content (CA)	9.6 %			
VOO	C content (OTC)	9.6 %			
Internationa	I Inventories				
Country	(s) or region	Inventory name		On inventory (yes/no)*	
Australia	1	Australian Inventory of	Chemical Substances (AICS)	Yes	
Canada		Domestic Substances	List (DSL)	Yes	
Canada		Non-Domestic Substan	nces List (NDSL)	No	
China		Inventory of Existing C	hemical Substances in China (IECSC)	Yes	
Europe		European Inventory of Substances (EINECS)	Existing Commercial Chemical	Yes	
Europe		European List of Notified Chemical Substances (ELINCS)		No	
Japan		Inventory of Existing a	nd New Chemical Substances (ENCS)	No	
Korea		Existing Chemicals Lis	st (ECL)	Yes	
New Zea	aland	New Zealand Inventor	у	Yes	
Philippin	es	Philippine Inventory of (PICCS)	Chemicals and Chemical Substances	Yes	
Taiwan		Taiwan Chemical Sub	stance Inventory (TCSI)	Yes	
United S	tates & Puerto Rico	Toxic Substances Cor	trol Act (TSCA) Inventory	Yes	
* ^ !!\/~~!!		nanta of this product comply	with the inventory requirements administered by th		

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	03-19-2019
Prepared by	Allison Yoon
Version #	01
Further information	CRC # 411A/1002393

	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc
Revision information	This document has undergone significant changes and should be reviewed in its entirety.



Certificate of Acceptability

Dear CRC[®] Valued Customer:

In 1998, the USDA Food Safety Inspection Service discontinued the testing of new and reformulated proprietary substances and nonfood compounds intended for use in USDA inspected food-processing facilities. In December of 1999, the National Sanitation Foundation (NSF), a non-profit, third party product certifier specializing in public health and safety, revived the USDA authorization program with the launch of their own Registration and Listing Program for Proprietary Substances and Non-Food Compounds. The NSF program is fee based and mirrors the previous USDA program evaluation for all product categories. Once a product has successfully gone through the NSF approval process, it receives a registration number. This registration number is listed on the label of the NSF registered product, along with the registration mark and category code.

CRC products authorized by the USDA before 1998 continue to meet USDA 1998 guidelines. Products introduced or modified after January 1999 are submitted to the NSF authorization process and carry the new NSF registration upon approval.

The following product is acceptable for use in inedible product processing areas, nonprocessing areas, and/or exterior areas of food processing establishments (C1) provided that it is not used to mask odors resulting from unsanitary conditions, and that any characteristic odor or fragrance does not penetrate into an edible product area. When used on equipment that will be returned to a food processing area, the product must be completely washed off and rinsed with potable water before returning to the processing area.

CRC Industries, Inc.