# DX0100M 100 ft (30.5 m)

## ТҮРЕ

#### U.S.C.G./SOLAS compliant lifering ropebags

### USES

Presented in a high visibility orange bag with the rope perfectly coiled for immediate and continual use. The bag features a handle for control whenever in use and also doubles as a hanger on the lifering bracket. Constructed of marine grade components and contains 100 feet of 3/8" floating hollow braided polypropylene.

### FEATURES

Meet or exceeds USCG requirements under 46 CFR 180.70 Rope Bag with 100ft of rope (30.5m) 3/8in hollow braided polypropylene Yellow rope

Floating rope

Minimum tensile strength of 3/8" hollow braid polypropylene rope is 1250 pounds

SPECIFICATIONS		
ITEM NO.	DX0100M	
USE	For regular lifering installations	
LENGTH OF ROPE	100ft (30.5 m)	
<b>COLOR OF ROPE</b>	Yellow	
<b>DIAMETER OF ROPE</b>	3/8″ (9.5 mm)	HANDLE
<b>TENSILE STRENGTH</b>	1250 lbs (567 kg)	DX0100M
WEIGHT	3 lbs (1.36 kg)	A loss for the second s
DIMENSIONS	16 x 7 x 4 in (40 x 18 x 10 cm)	Control Front Program Street S
<b>MOLD RESISTANT</b>	Yes	A Constant of the Constant of
HARDWARE	Marine grade	Contraction of the local division of the loc
<b>COLOR OF COVER</b>	International Orange	5
COVER	Coated heavy denier polyester shell fabric	1

### **APPROVAL/COMPLIANCE**

Life Saving Produc

Meet or exceeds USCG requirements under 46 CFR 180.70