

Product Specification Sheet

Woven Cord Strapping

Dr. Shrink, Inc.'s strapping is a composite strap made from high strength polyester fiber coated with a polymer binder. Strapping is used with wooden uprights and buckles to form the support structure under shrink wrap covers. It is also used to create the perimeter band that will secure the shrink wrap material. The strapping can be secured by hand-tying and using the appropriate wire buckles.

Standard core inside diameter is 3"

Strap width tolerance: +1/32", -3/32"

Part Number	Strap Width (inches)	Strap Length (feet)	Coil/roll Width	Color	Minimum Break Strength*	Rolls per case	Weight per roll (pounds)
Standard-duty							
DS-50015	1/2"	1500'	5 - 1/2"	White	600 lbf	10	7
DS-500	1/2"	3900'	5 - 1/2"	White	600 lbf	4	14
DS-750300	3/4"	300'	5 - 1/2"	White	900 lbf	1	2
DS-7501500	3/4"	1500'	5 - 1/2"	White	900 lbf	1	8
DS-750	3/4"	2100'	5 - 1/2"	White	900 lbf	4	15
Heavy-duty							
DS-50015HD	1/2"	1500'	5 - 1/2"	White	750 lbf	1	8
DS-500HD	1/2"	3900'	5 - 1/2"	White	750 lbf	2	20
DS-750HW	3/4"	1665'	5 - 1/2"	Yellow	1625 lbf	2	15
DS-1000HD	1"	1641'	5 - 1/2"	Orange	1881 lbf	2	17.5

**Unit of measure is 1 pound-force (lbf) which is equal to the gravitational force exerted on a mass of one avoirdupois pound (system of mass based on a pound of 16 ounces) on the surface of the Earth.*