

SPECIFICATIONS	N5100010A	N5100020A	N5100040A
<b>Wetted Parts</b>	Housing material - Acetal Copolymer	Housing material - Acetal Copolymer	Housing material - Acetal Copolymer
<b>Flow Rate</b>	Max Up to 2.5 (gpm) Max Up to 79.5 (lpm)	Max Up to 2.5 (gpm) Max Up to 79.5 (lpm)	Max Up to 2.5 (gpm) Max Up to 79.5 (lpm)
<b>Air Supply Pressure</b>	20 to 80 (psi) 1.4 to 5.6 (bar)	20 to 80 (psi) 1.4 to 5.6 (bar)	20 to 80 (psi) 1.4 to 5.6 (bar)
<b>Temperature Range</b>	40 - 120 (°F) 4.4 - 48.9 (°C)	40 - 120 (°F) 4.4 - 48.9 (°C)	40 - 120 (°F) 4.4 - 48.9 (°C)
<b>Self Priming</b>	Up to 28ft (8.5m)	Up to 28ft (8.5m)	Up to 28ft (8.5m)
<b>Port(s)</b>	Air Inlet & Outlet 1/4" (6.3 mm) Barb Liquid Inlet 3/8" (9.5 mm) Barb Liquid Outlet 3/8" (9.5 mm) Barb.	Air Inlet & Outlet 1/4" (6.3 mm) Barb Liquid Inlet 3/8" (9.5 mm) Barb Liquid Outlet 3/8" (9.5 mm) Barb.	Air Inlet & Outlet 1/4" (6.3 mm) Barb Liquid Inlet 3/8" (9.5 mm) Barb Liquid Outlet 3/8" (9.5 mm) Barb.
<b>Weight</b>	0.5 Kg (kg) 1.10 (lb)	0.5 Kg (kg) 1.10 (lb)	0.5 Kg (kg) 1.10 (lb)
<b>Diaphragm</b>	Buna	Viton®	Santoprene®
<b>Check Valve</b>	Buna	Viton®	Santoprene®

When it comes to quality boat pumps, Flojet is the brand you can depend on.