



a xylem brand

TUNGSTEN HALOGEN FLOODLIGHT

APPLICATION

JABSCO Tungsten Halogen Floodlights are designed to evenly light any horizontal surface. Unique trapezoidal light beam allows light to spread with even intensity when lamp is mounted from above at one end of a work area. Ideal for lighting deck or work surface from cabin top, spoiler or Tuna Tower. Great for R.V. use, such as lighting a campsite. Also ideal for emergency vehicles.

MOUNTING INSTRUCTIONS

Mount Light in location high enough to allow beam to spread adequately, such as Tuna Tower, rooftop or any convenient location where light will yield desired results. Drill 5/8" hole and use lock washer and nut provided to support light or if the mounting bracket has 3 holes, use self-tapping screws or other appropriate fastener to secure into position.

NOTICE: Light must be mounted in up position, with the words "sealed beam" at top of mounting. If bracket is desired at top of mounting, unscrew two screws at rear of housing, then turn light 180° and screw back together.



45900-Series

ELECTRICAL INSTALLATION

Use 14 AWG or larger stranded copper wire. 12 Volt model should have a 6 amp fuse (24 V, 3 amp) in positive side of wiring installation.

Model	Size	Volt	Watt	Bulb
45900-0000 (white)	4x6	12Vdc	50	45903-0000
45900-0001 (white)	4x6	24Vdc	70	45903-0001
45900-1000 (white)	3x5	12Vdc	50	45903-0002
45900-3000 (black)	3x5	12Vdc	50	45903-0002

THE PRODUCTS DESCRIBED HEREIN ARE SUBJECT TO THE JABSCO ONE YEAR LIMITED WARRANTY, WHICH IS AVAILABLE FOR YOUR INSPECTION UPON REQUEST.



a xylem brand