KICKER KMTC9 & KMTC11 HORN-LOADED TOWER SYSTEMS



Stitched polypropylene cone with Santoprene® surround

tweeter for extremely smooth sound

WHAT MAKES IT SUPERIOR?

-Industry-leading efficiency and SPL for loud, clear music while on the water

-Incredible low-end performance and bass extension

**From Top Of Bracket To Bottom Of Enclosure

-359-degree swiveling design without the need for tools

-Single-bolt removal system with no tools needed - store them away easily

-Clamps swivel to mount on curved tower bars (+/-5 degrees)

Model	КМТС9	KMTC11	
Woofer (in, mm)	9, 23	11, 28	
Horn Loaded Cempression Driver (in., mm.)	1, 25	1, 25	
Impedance (Ohms)	4	4	
Continuous Power (watts RMS)	300	300	
High Pass (dB), at Frequency (Hz)	12, 2500	12, 2500	
Low Pass (dB), at Frequency (Hz)	12, 2500	12, 2500	
Frequency Response (Hz)	20-20,000	20-20,000	
Enclosure Diameter (in., mm.)	9-13/16, 24.9	11-7/8, 30.2	
Enclosure Depth (in., mm.)	10-7/8, 27.7	12-11/16, 32.3	
Enclosure Height (in., mm.)	11-9/16, 29.4	13-5/8, 34.6	
Total Enclosure Height (in., mm.) *From Bottom Of Roll Bar	13-9/16, 34.4	15-9/16, 39.6	

Discover a comprehensive collection of marine speakers on our website.