Pro 5 MP Fire Extinguisher

Part number 466112 Multipurpose use

Rechargeable

UL Rated 3-A, 40-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro 5 MP unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough metal valve assembly.

Also available: 46611201 with Metal Strap Bracket.

At a Glance

- Model Pro 5 MP
- Multipurpose Dry Chemical
- UL listed
- UL rated 3-A, 40-B:C
- Supplied with wall hanger
- Monoammonium Phosphate 6 year limited warranty
- Suitable for use on most common fires

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 5.5 lb. of fire extinguishing agent (Average) 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with mounting bracket (not supplied)
- Powder coated cylinder for corrosion protection
- U.S.C.G. approved bracket part number 466400



Pt # 466112 - 4 pack UPC: 0-47871-66112-0 I2F - 20047871661125

For use on the following

types of fire:

Product Specification		
Net agent weight (Average)	5.5 lb.	
Unit weight (Average)	9.0 lb.	
Diameter	4.5 inches	
Height	16.31 inches	
Discharge time	13-15 seconds	
Discharge range	12-18 feet	
Operating pressure	195 psi	
Cylinder	Seamless aluminum	
Valve, handle, lever	Metal	
Strap Bracket	U.S.C.G approved	

Packaging Options



Packaging dimensions (inches)

	Depth	Width	Height
Carton	4.75	6.0	17.0
Master Pack	13.0	17.25	9.87

