

KJM is dedicated to providing the finest in shipboard equipment. Our products are built to withstand the harsh marine environment, and are designed by people with over three decades of experience in the marine industry. **Please read the following before attempting installation to ensure complete understanding of the Antenna.**

Supplied Parts

- 1 Antenna assembly
- 1 Grommet plug (see Tech Tips)

IMPORTANT! Please read all instructions before installing.

The A862-AMFM antenna of 8' overall length with a 20' cable with Motorola type plug attached.

Tools required: None.

Installation Instructions

Choose a mounting location as high as feasible, as free as possible from obstructions, and as far as possible from other antennas and strong sources of RF.

Mount the antenna according to the directions supplied with the mount you choose.

Route the antenna's cable to your AM/FM receiver and plug the Motorola type plug into the antenna jack. Coil any excess cable in a coil of at least 8" diameter and stow it in an out-of-the-way place.

To clean the antenna, use mild dishwashing liquid (one that is not harsh to the hands and *without ammonia*) in lukewarm water.

WARNING: Do not let paint solvents, cleaning solvents, or adhesive caulking come in contact with the antenna. Chemicals in these materials might destroy the finish.

For best performance:

Use optional AC301 20' cable to extend the length. Up to 2 AC301 cables can be connected.

One-section antenna

Cable

Tech Tips

This antenna will read "open circuit" when tested with an ohm meter or continuity tester.

For installations where the cable exits through the bottom center of the antenna's ferrule, replace the grommet at the exit hole in the ferrule with the supplied Grommet Plug.