

Edge Mount Trim Tab Kits

12-Volt / Single Actuator Kits



Edge Mount Trim Tab Kits

12-Volt

Designed for boat applications where a lower actuator mounting height is desirable. Actuator mounts at the trailing edge of the blade giving it a 1/2" (1.3 cm) lower mounting height on 9" (22.9 cm) long blades & 3" (7.6 cm) lower mounting height on 12" (30.5 cm) long blades. All edges are turned up for added strength and style. Boat lengths 14' (4.3 m) to 36' (11 m).



Blades are constructed of 12 gauge (2.7 mm) laser cut 304 stainless steel with 1" (2.5 cm) turned up edges and a 5 degree taper on both sides to the trailing edge, & 1/8" (3.2 mm) diameter hinge pin. Upper and lower high impact corrosion proof mounting brackets with mechanical cable gland seal.

Kits include:


- ▶ (2) 12-gauge stainless steel standard finish blades
- ▶ (2) 15054-001 actuators with 6' (1.8 m) leads and Deutsch connectors
- ▶ (2) 30133-103 actuator extension wiring harnesses - 20' (6.1 m) length
- ▶ (2) 15085-001 upper mounting brackets with gland seal
- ▶ (2) 50014-001 lower mounting brackets
- ▶ Lenco owner's/installation manual
- ▶ Stainless steel mounting hardware



SIZE DESCRIPTION

- Ⓛ = Length of tab
- Ⓜ = Width of hinge

Size description to be used with chart below.



Retail Box

See check-list below



Electro-Polished Edge Mount Trim Tab Kits

12-Volt

All the same features of the Edge Mount series with the addition of Electro-Polished blades. Electro-Polish adds a mirror finish and the ultimate corrosion protection. Actuator mounts at the trailing edge of these 12" (30.5 cm) blades giving them a 3" (7.6 cm) lower mounting height. Boat Lengths 14' (4.3 m) to 30' (9.1 m).



Blades are constructed of Electro-Polished 12 gauge (2.7 mm) laser cut 304 stainless steel with a 1" (2.5 cm) turned up edges and a 5 degree taper on both sides to the trailing edge & 1/8" (3.2 mm) diameter hinge pin. Upper and lower high impact corrosion proof mounting brackets with mechanical cable gland seal.

Kits include:


- ▶ (2) 12-gauge stainless steel Electro-Polished blades
- ▶ (2) 15054-001 actuators with 6' (1.8 m) leads and Deutsch connectors
- ▶ (2) 30133-103 actuator extension wiring harnesses - 20' (6.1 m) length
- ▶ (2) 15085-001 upper mounting brackets with gland seal
- ▶ (2) 50014-001 lower mounting brackets
- ▶ Lenco owner's/installation manual
- ▶ Stainless steel mounting hardware



SIZE DESCRIPTION

- Ⓛ = Length of tab
- Ⓜ = Width of hinge

Size description to be used with chart below.



Retail Box

See check-list below



Edge Mount Trim Tab Kits - 12-volt

Lenco Part#	L" X W"	Boat Length	Hinge Height	Min.Transom Height	Retail Box
15013-101	9" X 9"	14' - 18'	2" (5.1 cm)	13.5" (34.3 cm)	✓
15014-101	9" X 12"	16' - 25'	2" (5.1 cm)	13.5" (34.3 cm)	✓
15015-101	12" X 9"	14' - 18'	2" (5.1 cm)	11" (27.9 cm)	✓
15016-101	12" X 12"	17' - 30'	2" (5.1 cm)	11" (27.9 cm)	✓
15017-101	12" X 18"	26' - 36'	2" (5.1 cm)	11" (27.9 cm)	✓

Edge Mount Electro-Polished Trim Tab Kits - 12-Volt

Lenco Part#	L" X W"	Boat Length	Hinge Height	Min Transom Height	Retail Box
15115-101	12" X 9"	14' - 18'	2" (5.1 cm)	11" (27.9 cm)	✓
15116-101	12" X 12"	17' - 30'	2" (5.1 cm)	11" (27.9 cm)	✓

SWITCH KITS SOLD SEPARATELY

See page 20 through 21.

SWITCH KITS SOLD SEPARATELY

See Lenco catalog page 20 through 21

Learn more about trim tabs, hydrofoils and thrusters we have.

WE MAKE THE BEST BOATS BETTER!