



## SNOWMOBILE OIL CODES 11462

**Color: Blue-Green**

**LUBRIMATIC SNOWMOBILE OIL** is a high quality oil for Air-Cooled engines. It is formulated using high viscosity index paraffinic bas oils and selected Ashless additives to provide rust and corrosion inhibition and minimize preignition, ring sticking port and spark plug deposits, as well as combustion chamber deposits. It meets the performance requirements for API service TC/JASO FB. It is NMMA (formerly BIA) certified for performance level TCW-3®. It is also suitable for TA, TB, TC, TD, TC-W, TC-WII, AND TCW service.

**LUBRIMATIC SNOWMOBILE OIL** is specially developed for use in snowmobiles, ATV's, motorcycles, chainsaws, lawnmowers, air blowers, string trimmers, jet ski's, and other equipment requiring metered oil injection or fuel oil mixing. It provides easy mixing. It provides easy mixing and stable mixtures with gasoline, event at low temperatures. It meets the performance requirements of high performance engines found in motorcycles and snowmobiles such as Yamaha, Suzuki, Honda, Kawasaki, Bombardier/Skisoo, Polaris, Artic Cat as well as high performance engines such as Chrysler, Evinrude, Force, Johnson, Mariner, Mercury, OMS, Sears, Suzuki, and Yamaha engines. Consult your lubrication Recommendation Guide for further infomration on specific application.

**Brief product description:** This two-cycle oils is formulated to be used in high temperature, two-cycle engines, such as air cooled engines. This oil should be mixed to the proper fuel/oil ratio as recommended by the engine manufacturer.

<b><u>Test</u></b>	<b><u>ASTM Method</u></b>	<b><u>Typical Results</u></b>
Base Oil Characteristics		
Vis @ 40° cSt	D-445	36.73
Vis @ 100° cSt	D-445	6.40
Viscosity Index	D-2270	126
Pour Point, °F	D-97	-40 (-40)
Flash Point, °F	D-93	104
Gravity, API	D-287	31.8

**Date: November 15, 2011**