
Data Sheet | 2018





$\frac{\text{SUPRA Series - Dual Color}}{\text{SURFACE MOUNT UNDERWATER LED LIGHT}}$



PART DESCRIPTION	SUPRA SMX23 SURFACE MOUNT UNDERWATER LED LIGHT
Part Number	60-0313
Available Colors	Dual Color (Blue & White)
Lumens	5,625
Fixture Lumens (White)	2,500
Number & Type Of LED	White-9×5W / Blue-12×3W
LED Power - HICOB Array	Yes
Typical LED Life	50,000+ Hours
Warranty	2 Years
User Control Options	On/Off Switch (Third party supplied)
Electrical Installation	Simple 2 Wire Connection
Compact Size	Diameter: 70mm (2.75") Height: 17mm (0.67")









Data Sheet | 2018



SUPRA Series - Dual Color SMX23 SURFACE MOUNT UNDERWATER LED LIGHT

Dual Color

TECHNICAL	
Driver	Multi-Channel Internal Driver
Supply Voltage Range (12 V ONLY)	10.5–14.5 V DC
Max Current Draw 12V	2.5 A
Surge Protection	Yes (3,000V)
ATRB (Automatic Thermal Roll- Back)	Yes
Low Voltage Protection	Automatic Voltage Roll-Back Control And Low Voltage Cut Out
Auto Power Control	Yes – Intelligent Multi-Channel Power Management
"Soft Start" Electronics Protec- tion	Yes
Reverse Polarity Protection	Yes
In Rush Current Protection	Yes
Power Line Noise Suppression	Yes
Bonding	Not Required
Electrical Installation	Simple 2 Wire Connection
Max Vessel Length	7.5m (25')

LIGHTING SYSTEM FUNCTIONALITY (ON/OFF SWITCH)ModeSwitch Off/On to move
to the next modeStart Up (Lights come on in White Mode first)YesSelectable Modes (Toggle switch to advance)YesPreset Colors (White and Blue)YesStrobe (White and blue in a strobe pattern)YesFade (White and Blue in a fade pattern)Yes

PHYSICAL

FILISICAL	
Beam Angle	90°
Water Ingress Protection Rating	IP68
Light Face Diameter	70mm (2.75")
Profile (Height) Of Housing	17mm (0.67")
Housing Type	Marine Bronze Body with Borosilicate Glass Lens
Light Cable Length	2m (6'6'') Standard (Can be extended *)
Hole Cut-Out for Cable (Drill bit size)	Metric: 13.5mm Imperial: 17/32" (0.5313")
Weight	350g (0.77 Lbs)
Mechanical Installation	3 x Marine Bronze Screws (Provided)

* Extension distance depends on cable type, refer to user manual for further information