



## Colours TH **HD** Gen2

High Definition Underwater Lighting Excellence

Colours by OceanLED are the first high-powered color change underwater LED lights for boats that allow boat owners to choose the color of their lights from an unlimited color pallet, and now they're even brighter!

Colours utilize the very latest 4-channel RGBW (Red/Green/Blue/White) High Definition LEDs. Controlled via DMX-512 through the vessels onboard systems, or wirelessly via third party devices such as an iPad, iPhone or Android, Colours allows you to preprogram more than 40 static and dynamic color scenes to set the mood, enhance an onboard event, strobe to attract fish, or even change color with the time of day.

The Colours Thru-Hull model with the world's smallest hole cut-out for a thru hull light at only 1" and a 1-inch (25mm) profile head make it the ideal underwater light for transom mount applications.

Suitable for all hull types up to and over 65' (20m) using 2-6 lights with spacing of 3-5' (1-1.5m) - for metal hulls, add the Delrin Isolation Sleeve accessory. Deutsch plug-and-play quick connectors make this light a quick fit. Maintenance is easy; just wipe away marine growth from its scratch resistant Tritonium™ glass lens.

For a color-change light with a lower profile head for hull mount applications, or that can be exchanged without hauling, choose Colours XFM. Single-color models are also available.

See reverse side for additional parts required for Colours models.

**NEW!**

OceanLED Marine  
Pro Series **HD Gen2**



Underwater  
**ColoursTH**



- 1" Hole in Hull
- Equal to 250W HID/Metal Halide
- 110-240V AC
- 40,000+ Hour Life
- Aluminium Bronze AB2
- Plug & Play
- Factory Sealed Unit
- No Breakable Parts

### Quick Specs

<b>40K HOURS</b>	<b>110V AC</b>		<b>Tritonium</b>	<b>REVERSE POLARITY PROTECTION</b>	<b>DMX COMPATIBLE</b>
<b>LIFE SPAN</b>	<b>240V AC</b>	<b>60/140°</b> <small>PRIMARY/SECONDARY BEAM</small>	<b>OPTICAL LENS</b>		

Description	Color	Part #	UPC/EAN #
Pro Series COLOURS TH <b>HD</b> Gen2 LEDs w/Linear Optics		001-500733	5051803005452

Mounting Recommendations	Colours TH <i>HD Gen2</i>
Boat size	up to and over 65' (20m)
Transom / Hull spacing	3-5' (1-1.5m)
Transom quantity	2-6
Maximum hull thickness	3 <sup>1</sup> / <sub>2</sub> " (90mm)
Installation depth (to top of fixture)	8-10" (200-250mm)
Technical	
Light output equivalent to	250W HID Metal Halides
Typical LED life expectancy	40,000+ Hours
Minimum-Maximum operating voltage AC (AC/only)	90-270V AC
Current / Amp draw (AC/only)	110V AC 50/60HZ 1.1A 240V AC 50/60HZ 0.5A
Approx. light penetration (avg. water quality)	59' (18m)
Approx. Light penetration (perfect water quality)	up to 140' (45+m)
Driver type	External
Driver size (L x W x H)	360 x 160 x 90mm (14 <sup>3</sup> / <sub>16</sub> x 6 <sup>1</sup> / <sub>4</sub> x 3 <sup>1</sup> / <sub>2</sub> "
Physical	
Diameter of fixture	5 <sup>1</sup> / <sub>2</sub> " (140mm)
Profile (height) of fixture	17/32" (30.8mm)
Total weight including electrical driver	5.5lbs (2.5kgs)
Extension cable length (standard-hard wired to light)	6 <sup>1</sup> / <sub>2</sub> ' (2m)
Hole cut-out for cable entry	1" (26mm)
Material	Aluminium Bronze AB2
Lens	Tritonium™ Optical Lens
Accessories	
	Part#
Delrin Isolation Sleeve for 2010/COLOURS Thru-Hull	001-500164
Locking Nut Kit for All Thru-Hull Models	050-000029
2m (6.5') Plug & Play Extension Cable (Gen2)	001-500753
6m (19.5') Plug & Play Extension Cable (Gen2)	001-500754
IP68 Ethernet DIY Cap	001-500463
Pro Series <i>HD Gen2</i> Colours Driver & Ethernet Connection Cable	001-500756
Ethernet Colours Connection Cable (3 Meter) (Included w/COLOURS Driver)	001-500594
Colours Terminator Kit (Included with DMX Controller)	001-500467
*Add'l required parts for Colours models	
	Part#
DMX Touch Panel Controller (includes 1 Terminator Kit)	001-500596
DMX Wi-Fi Touch Panel Controller (includes 1 Terminator Kit)	001-500598

**\*PARTS REQUIRED FOR COLOURS MODELS:** When installing Colours models you will need to purchase separately one (1) DMX Touch Panel Controller or one (1) DMX Wi-Fi Touch Panel Controller. For complete installation information refer to the Pro Series HD Installation Manual.

## OceanLED Smart Light Technology

All OceanLED lights are factory sealed, essential for lighting components subjected to the corrosive marine environment.

### Active Thermal Control

ATC is a continuous monitoring system built into all OceanLED lighting products to prevent overheating, thus improving LED performance and lumen maintenance. In the event the lights become overheated, the ATC system will reduce the LED power level in order to protect the LEDs, or in extreme cases, turn off the fixture completely.



### Grade A Electrical Performance

OceanLED utilizes the very latest optical methods to achieve the highest Lumen Per Watt efficacy ratings on all its products. Combining optical precision with Grade A Electrical components ensures maximum life cycles, minimal heat exposure, and flicker free operation and dimming.



### OceanLED Binning Promise

Millions of LEDs are produced every day, some better than others. LEDs are sorted or "Binned" according to their light output, emitted color, and electrical efficiency. OceanLED specifies only premium binned LEDs to ensure the highest quality and color intensity.

### Contents include:

- Colours TH HD Underwater LED Light w/Cable
- Mounting Kit
- Colours AC Driver w/Cable
- Ethernet Connection Cable



**OceanLED**<sup>®</sup>



Learn more about boat underwater lights we have.