## EPIXOR XT

## **EPIXOR XT SPINNING REELS FEATURE:**

- TCA: C40x carbon Torsion Control Armor reduces twisting
- Multi-disc, Japanese oiled felt drag washers
- 7BB+1RB stainless steel bearings
- Quick-Set ant-reverse bearing
- Precision machine cut brass pinion gear
- Slow oscillation system for improved line lay
- Corrosion resistant graphite body and rotor
- CFR: Cyclonic Flow Rotor technology
- Rigid metal handle design for strength
- Machined aluminum, 2-tone anodized spool with LCS lip
- Heavy duty solid aluminum bail wire
- RESII: Computer balanced Rotor Equalizing System

















7 FLOW SOLLAND 44





## **EPIXOR XT**

	Model	Gear ratio	Bearings	Weight (g)	Line retrieve (cm)	Max Drag Force (kg)	Monofilament line capacity (diameter in mm.)	Braided line rating (Tuf line)	Frame	Sideplates	Rotor	Spool
NEW	EPXT-20	5.0:1	7BB+1RB	208	60.7	5	0.15/250,0.20/140,0.25/90	N/A	C-40X	GR	GR	AL
NEW	EPXT-30	5.0:1	7BB+1RB	249	68.7	8	0.2/300,0.25/200,0.30/130	215/15	C-40X	GR	GR	AL
NEW	EPXT-40	5.0:1	7BB+1RB	304	76.3	10	0.25/260,0.30/180,0.35/130	200/30	C-40X	GR	GR	AL
NEW	EPXT-50	5.0:1	7BB+1RB	311	81	8	0.30/230, 0.35/170, 0.40/130	200/30	C-40X	GR	GR	AL