

## Navigation Light Sets

### Base Mount 2 Mile/3 Mile Certified (USCG 2nm/3nm)

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Polymer  
 Finish: Black or White  
 Dimensions: Height: 4-7/8", O.D. Base: 3-5/16",  
 Screw Size: #10  
 Voltage: 12 or 24V (Bulb Included)  
 Wattage: Bulb: 25 watt or 10 watt  
 Amperage: 25 watt                      10 watts  
                   12V: 2.08 amps            12V: .83 amps  
                   24V: 1.04 amps                24V: .42 amps

**Fig. 0200**  
**Base Mount**  
**Green**  
**Side Light**



**Red**  
**Side Light**

**Stern**

**Green**  
**All-Round**

Base Mount	Visibility Arc	Black Retail Pkg.	White* Std. Pkg.	Visibility Miles	Replacement Bulb
Bi-Color Light	225°	0200BB0DP1	0200BB0W01	2	037512V25W
Red Side Light	112-1/2°	0200PB0DP1	0200PB0W01	2	037512V25W
Green Side Light	112-1/2°	0200SDBDP1	0200SDBW01	2	037512V25W
White Masthead Light	225°	0200MB0DP1	0200MB0W01	3	037512V25W
White Stern Light	135°	0200SNBDP1	0200SNBW01	2	037512V10W
Yellow Towing Light	135°	0200TWBDP1	0200TWW01	2	037512V10W
White All-Round Light	360°	0200SWBDP1	0200SWBW01	2	037512V10W
Red All-Round Light	360°	0200SRBDP1	0200SRBW01	2	037512V25W
Green All-Round Light	360°	0200SGBDP1	0200SGBW01	2	037512V25W
Tri-Color Light**	360°	0200TB0DP1	0200TB0W01	2	037512V25W

\* 12 Volt Only

\*\* Use For Vessels Under Sale Alone

For Pipe Mounting Bracket options, see Figs. 0222 & 0224 on page 27.

### Top Mount 2 Mile/3 Mile Certified (USCG 2nm/3nm)

Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Black or White Polymer  
 Stainless Steel Mounting Bracket Included  
 Dimensions: Height: 4-13/16", O.D.: 3-5/16", Projection: 3-5/16"  
 Screw Size: #10  
 Voltage: 12 or 24V (Bulb Included)  
 Wattage: Bulb: 25 watt or 10 watt  
 Amperage: 25 watt                      10 watts  
                   12V: 2.08 amps            12V: .83 amps  
                   24V: 1.04 amps            24V: .42 amps

**Fig. 0200**  
**Top Mount**  
**Masthead**



**Red**  
**Side Light**

**Stern**

**Towing**

Top Mount	Visibility Arc	Black Retail Pkg.	White* Std. Pkg.	Visibility Miles	Replacement Bulb
Bi-Color Light	225°	0200BT0DP1	0200BT0W01	2	037512V25W
Red Side Light	112-1/2°	0200PT0DP1	0200PT0W01	2	037512V25W
Green Side Light	112-1/2°	0200SDTDP1	0200SDTW01	2	037512V25W
White Masthead Light	225°	0200MT0DP1	0200MT0W01	3	037512V25W
White Stern Light	135°	0200SNTDP1	0200SNTW01	2	037512V10W
Yellow Towing Light	135°	0200TWTDP1	0200TWTW01	2	037512V10W

\* 12 Volt Only

### Ordering Info - For 24V (Black Only) on pages 26 and 27

Note: For 24V Lights, Replace the "DP1" with "DP2". For the Replacement Bulb, Replace the "12V" with "24V" (e.g., 037524V25W).

For 32V Lights: Contact the Factory.