



Horizontal Mount Bi-Color Lights

LED 2-mile (USCG 2nm) Certified - Patent #D665,113S
Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Stainless Steel
Finish: Polished, Black, or White Powder Coated
Dimensions: Length: 2-1/2", Width: 2-5/8", Height: 5/8"
Screw Size: #8
Voltage: 12V LED
Wattage: 3.75 watts
Amperage: <0.25 amps
Features: Ultra Low Profile, Low Heat, Long Life



STEALTH II Series
Fig. 0615 Stainless

Navigation Lights

Finish	Retail Pkg.	OEM Bulk Pkg.
Polished SS	0615DP2STS	0615000STS
Black	0615DP2BLK	0615000BLK
White	0615DP2WHT	0615000WHT

Spare gasket kit required for mounting on metallic surfaces (optional for fiberglass surfaces and included in DP package): 0615000GKT



Black

White



2-mile (USCG 2nm) Certified
Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Bronze Top, Polymer Base
Finish: Chrome, Black, or White
Dimensions: Length: 3-1/2", Width: 2-1/4", Height: 1-5/8"
Screw Size: #8
Contacts: Gold Plated
Voltage: 12V (Bulb Included)
Wattage: 10 watts
Amperage: .80 amps



Fig. 0252 Chrome

Finish	Retail Pkg.	OEM Bulk Pkg.
Chrome	0252MB0DP1	0252MB012V
Black	0252BB0DP1	0252BB012V
White	0252WB0DP1	0252WB012V



White

Black



Note: Fig. 0252 can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior. Replace the bulbs provided with Cat. No. 0072DP1CLR 24-volt bulbs. Contact us for 24-volt applications on new construction.

Fig. 0252:
Bulbs: 0071DP0CLR.
Lens: 0247DP0LNS.
Black Base with Socket Assembly: 0114000BLK.
White Base with Socket Assembly: 0114000WHT.

Spare Parts Information



Fig. 0247DP0LNS



Fig. 0071DP0CLR

L.E.D.'s have no user serviceable parts