

The above lights are for replacement use only on sail or power driven vessels under 20 meters (65.6 ft.) in length, and operating on a nominal 12 volt system. All previous certifications apply. In order to comply with the '72 COLREGS* and the U.S. Inland Rules*, the following must be adhered to:

MOUNTING INFORMATION

Read all instructions before proceeding.

- 1). These instructions show the orientation of the light after the proper location has been determined. For proper light selection, positioning and configuration, refer to the A.B.Y.C. Standard A-16*, the '72 COLREGS*, and the U.S. Inland Navigation Rules*.
- 2). This light is supplied with the proper bulb for operation on a nominal 12 volt system. Use PERKO Cat. No. 0070DP0CLR, 12V, 10W bulb for a 12 volt system (Stern Light Cat. No. 093900112V or 0939DP112V).
- 3). These Lights are designed to be mounted on a vertical surface that is perpendicular to the centerline of the boat and facing astern.
- 4). Draw an 8 inch long horizontal reference line through the center of the selected mounting location.
- 5). Cut out the mounting template below. Tape it on the mounting surface such that the reference line (drawn above) passes through the exact center of the template.
- 6). Drill two holes through the template as indicated for the mounting screws.
- 7). Drill a 2-1/8 inch hole to accommodate socket holder as indicated.
- 8). Attach supply connections to the light, making sure to wire in accordance with both A.B.Y.C. Standard E-9* and U.S. Coast Guard Safety Standards for Boat Electrical Systems (33 CFR 183)*

MOUNTING TEMPLATE

