Combination Masthead/White All-Round Navigation Lights -Plug-in Mount Bases

3-mile (USCG 3nm) Certified

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

Material:	Figs. 1123/24: Polymer Top and Zinc Alloy Fig. 1125: Polymer Top and Zinc Alloy Top, Brass Base Fig. 1625: Polymer Top and Zinc Alloy Top, Brass Base	
Finish:	Black and Chrome Plated	
Contacts:	Gold Plated	
Tube:	3/4" Anodized Aluminum	
Screw Size:	#8	
Voltage:	12V LED	12V Incandescent (two bulbs incl.)
Wattage:	2.2 watts (ea. compartment)	10 watts (each compartment)
Amperage:	0.2 amps. (ea. compartment)	80 amps (each compartment)

Features: Two light compartments (Masthead/Anchor)

- Fig. 1123: Horizontal mount
- Fig. 1124: Vertical mount
- Fig. 1125: Deck mount plug-in base with waterproof cover for base that attaches to deck mounted retainer when light is in place.
- Fig. 1625: LED light, deck mount plug-in base with waterproof cover for base that attaches to deck mounted retainer when light is in place. (See wiring note below.)

Horiz. Mt.

Fig. 1123
45° Rake

Fig. 1124
45° Rake

Vert. Mt.

Fig. 1125
16° Rake

Fig. 1625
16° Rake

Cover

Retainer

PROP 65 WARNING (Contains Lead)

CE

Navigation Lights

Base Mount	Approx. Pole Length	Pole Rake	Base Dimensions	Retail Pkg.	OEM Bulk Pkg.
Horiz. Mt.	15"	45°	2-1/4" x 3/4"	1123DP1CHR	1123001CHR
Horiz. Mt.	28"	45°	2-1/4" x 3/4"	1123DP2CHR	1123002CHR
Vert. Mt.	15"	45°	3/4" x 2-1/4"	1124DP1CHR	1124001CHR
Vert. Mt.	28-3/4"	45°	3/4" x 2-1/4"	1124DP2CHR	1124002CHR
Deck Mt.	35-7/8"	16°	3-3/8" x 2-1/4"	1125DP4CHR	1125004CHR
Deck Mt. LED	34-5/8"	16°	3-3/8" x 2-1/4"	1625DP4CHR	1625004CHR

Fig. 1625 L.E.D.'s have no user serviceable parts

Fig. 1625 Wiring Note: When choosing LED upgrades to replace existing incandescent combination masthead/all-round lights, optional Cat. No. 1680DP012V Converter Module is available to avoid re-wiring the navigation light switch.



Fig. 1680DP012V

Spare Parts Information

Figs. 1123, 1124 & 1125:
12V Bulbs: 0071DP0CLR.
Cap for Base: 0125DP0BLK
Lenses (2 per card): 0278DP0WHT.
Top Cap with Screw: 1158DP0BLK.
Replacement Pole Size 1: 1123DP199A.
Replacement Pole Size 2: 1123DP299A.

Fig. 1123 Base with Socket Assembly: 1123DP099A.
Fig. 1124 Base with Socket Assembly: 1124DP099A.
Fig. 1125/1625 Base with Socket Assembly: 1125DP099A.
Fig. 1125 Replacement Pole Light : 1125DP499A.

Fig. 1123

Fig. 1124

Fig. 1125

Fig. 0278

Fig. 0071DP0CLR