

Combination Masthead/White All-Round Navigation Lights

3-mile (USCG 3nm) Certified

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Polymer Top and Base, Zinc Alloy, Clear Polymer Lens and 3/4" Anodized Aluminum Tube
 Finish: Black and Chrome Plated
 Contacts: Gold Plated
 Screw Size: #8
 Voltage: 12V (Two Bulbs Included)
 Wattage: 10 watts (each compartment)
 Amperage: .80 amps (each compartment)

Features: Two light compartments (Masthead/Anchor)

- Fig. 1183: **Fixed Mount** - one pole length
- Fig. 1196: **Fixed Mount** - two pole lengths
- Fig. 1197: **Fixed Mount Short Pole** - with pigtail leads
- Fig. 1201: **Fixed Mount** - Tri-color light

Fold-Down Mts: Feature adjustable angle (0° to 180°) for poles less than 18" long, include adapters available for flat or "V" type 45° mounts and a notch for through base wiring.

- Fig. 1181: **Horizontal Mount** - Folds down 90° in either direction opposite the plane of attachment plate of the mount.
- Fig. 1184: **Vertical Mount** - Folds down 90° in either direction along the plane of attachment plate of the mount.

1196 Head Style



Fig. 1184
Vertical Mt.
(Shown)

Fixed & Folding Mount Options



Fig. 1181
Horizontal Mount



Fig. 1184
Vertical Mount



Fig. 1197
Fixed Mt.
Short Pole



Figs. 1183
and **1196**
Fixed Mount



Base Mount	Height Overall	Base Dimensions	Retail Pkg.	OEM Bulk Pkg.
Fixed Mt.	4"	1" x 2-5/8"	1183DP0CHR	1183000CHR
Fixed Mt.	6"	1" x 2-5/8"	1196DP1CHR	1196001CHR
Fixed Mt.	12-3/16"	1" x 2-5/8"	1196DP2CHR	1196002CHR
Fixed w/Pigtail	4-7/8"	3/4" Dia.	1197DP0CHR	1197000CHR
Folding				
Horiz. Mt.	14-1/4"	2" x 1-1/2"	1181DP0CHR	1181000CHR
Vert. Mt.	14"	2-1/4" x 5/8"	1184DP0CHR	1184000CHR
Tri-Color Light				
Fixed Mt.	4-1/8"	1" x 2-5/8"	1201DP0BLK	-----

Tri-Color Light 2-mile (USCG 2nm) Certified

Use on Vessels Under Sail Alone Under 12m (39.4 ft.) in Length



Fig. 1201

NOTE: All of the above can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior to 11/1/03. Replace the bulbs provided with Cat. No. 0072DP1CLR 24-volt bulbs. Contact us for 24 volt applications for new construction.

Spare Parts Information

12V Bulbs: 0071DP0CLR.
 Lenses: 0278DP0WHT.
 Top Cap with Screw: 1158DP0BLK.

Fig. 1201: Bi-Color Lens Set (Red/Green): 0268DP0LNS.



Fig. 0071DP0CLR



Fig. 0268



Fig. 0278