PERKO[®]



Combination Masthead/White All-Round Navigation Lights

3-mile (USCG 3nm) Certified

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Polymer Top and Base, Zinc Alloy, Clear

Polymer Lens and 3/4" Anodized Aluminum Tube

Finish: Black and Chrome Plated

Contacts: Gold Plated

Screw Size: #8

Voltage: 12V (Two Bulbs Included) 10 watts (each compartment) Wattage: Amperage: .80 amps (each compartment)

Features: Two light compartments (Masthead/Anchor)

> Fig. 1183: Fixed Mount - one pole length Fig. 1196: Fixed Mount - two pole lengths

Fig. 1197: Fixed Mount Short Pole - with pigtail leads

Fig. 1201: **Fixed Mount** - Tri-color light

Fold-Down Mts: Feature adjustable angle (0° to 180°) for poles less

than 18" long, include adapters available for flat

or "V" type 45° mounts and a notch for through base wiring.

Fig. 1181: Horizontal Mount - Folds down 90° in either direction

opposite the plane of attachment plate of the mount. **Vertical Mount** - Folds down 90° in either direction along

the plane of attachment plate of the mount.

Fixed & Folding Mount Options



Fig. 1181 Horizontal Mount



Fig. 1184 Vertical Mount



Fig. 1197 Fixed Mt. **Short Pole**



Figs. 1183 and 1196 **Fixed Mount**





Fig. 1184 Vertical Mt. (Shown)





	Height	Base		
Base Mount	Overall	Dimensions	Retail Pkg.	OEM Bulk Pkg.
Fixed Mt.	4"	1" x 2-5/8"	1183DP0CHR	1183000CHR
Fixed Mt.	6"	1" x 2-5/8"	1196DP1CHR	1196001CHR
Fixed Mt.	12-3/16"	1" x 2-5/8"	1196DP2CHR	1196002CHR
Fixed w/Pigtail	4-7/8"	3/4" Dia.	1197DP0CHR	1197000CHR
Folding				
Horiz. Mt.	14-1/4"	2"x 1-1/2"	1181DP0CHR	1181000CHR
Vert. Mt.	14"	2-1/4" x 5/8"	1184DP0CHR	1184000CHR
<u>Tri-Color Light</u>				
Fixed Mt.	4-1/8"	1" x 2-5/8"	1201DP0BLK	

Tri-Color Light 2-mile (USCG 2nm) Certified Use on Vessels

Under Sail Alone Under 12m (39.4 ft.) in Length

Fig. 1201



NOTE: All of the above can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior to 11/1/03. Replace the bulbs provided with Cat. No. 0072DP1CLR 24-volt bulbs. Contact us for 24 volt applications for new construction.

Spare Parts Information







Fig. 0278

