



Vertical Mount Side Lights

2-mile (USCG 2nm) Certified

Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Zinc Alloy
 Finish: Chrome Plated
 Dimensions: Length: 3-1/2", Width: 2-1/4", Projection: 1-3/8"
 Screw Size: #8
 Contacts: Gold Plated
 Voltage: 12V (Bulb Included)
 Wattage: 8 watts (each light)
 Amperage: .70 amps (each light)

Finish	OEM Bulk Pkg.*
Chrome	0264M0012V



Fig. 0264



*Sold in pairs.

1-mile (USCG 1nm) Certified

Use on Sail or Power Driven Vessels Under 12m (39.4 ft.) in Length

Material: Brass or Stainless Steel Top, Polymer Base
 Finish: Chrome Plated or Polished
 Dimensions: Length: 4-1/4", Width: 2-3/8", Projection: 1-9/16"
 Screw Size: #4
 Contacts: Gold Plated
 Voltage: 12V (Bulb Included)
 Wattage: 10 watts (each light)
 Amperage: .80 amps (each light)

Finish	Retail Pkg.*	OEM Bulk Pkg.*
Chrome	0955DP0CHR	0955000CHR
Polished SS	0955DP0STS	0955000STS



Fig. 0955



*Sold in pairs.

1-mile Certified A-16 for replacement use only

Use on Power Driven Vessels Under 12m (39.4 ft.) in Length

Material: Zinc Alloy Top, Vinyl Gasket
 Finish: Chrome Plated
 Dimensions: Length: 5-1/2", Width: 3-1/8", Projection: 1-3/4"
 Contacts: Gold Plated
 Screw Size: #8
 Voltage: 12V (Bulb Included)
 Wattage: 10 watts (each light)
 Amperage: .80 amps (each light)

Finish	Retail Pkg.*
Chrome Zinc	1264DP0CHR



Fig. 1264



*Sold in pairs.

NOTE: All the above can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior. Replace the bulbs provided on Figs. 0955 & 1264 with Cat. No. 0072DP1CLR and Fig. 0264 with 0072DP8CLR 24-volt bulbs. Contact us for 24-volt applications on new construction.

Spare Parts Information

FIG. 0264:
 Green Lens Only: 0277DPGLNS.
 Red Lens Only: 0277DPRLNS.
 Base w/Socket Assy: 0254BLK99A.
 Bulbs: 0071DP8CLR



Fig. 0277



Fig. 0071DP8CLR

FIG. 1264:
 Green Side Light: 1264G00CHR.
 Red Side Light: 1264R00CHR.
 Lens Set: 1264DP0LNS.
 Socket Assembly: 1264DP099A.
 Bulbs: 0071DP0CLR.



Fig. 0071DP0CLR

FIG. 0955:
 Chrome Brass Green Side Light: 0955G00CHR.
 Chrome Brass Red Side Light: 0955R00CHR.
 Stainless Green Side Light: 0955G00STS.
 Stainless Red Side Light: 0955R00STS.
 Base with Socket Assembly: 095500099A.
 Lens Set: 0260DP0LNS.
 Bulbs: 0071DP0CLR.



Fig. 0260DP0LNS