

The above lights are designed for use on power driven vessels under 12 meters (39.4 ft.) in length, operating on a nominal 12 volt system. In order to comply with '72 COLREGS and the U.S. Inland Navigation Rules, the following must be adhered to:



MOUNTING INFORMATION
 Read all instructions before proceeding.

- 1). These instructions show the orientation of the light after the proper mounting location has been determined. For proper light selection, positioning and configuration, refer to A.B.Y.C. Standard A-16*, the 72 COLREGS*, and the U.S. Inland Navigation Rules*. These lights are supplied complete with 12 volt bulbs (Cat. No. 0338DP1CLR 12V, 5W).
- 2). These lights are designed to be mounted on a horizontal, vertical or angled surface. Adhere to instruction #8 below, while selecting the appropriate mounting surface.
- 3). a). Cat. No. 1281000CHR & 1281DP0CHR: Draw a 3 inch long reference line through the center of the selected mounting location and parallel to the vertical plane through the fore-aft centerline of the boat.
 b). Cat. No. 1284000CHR & 1284DP0CHR: Draw a 4 inch long reference line through the center of the selected mounting location and parallel to the vertical plane through the fore-aft centerline of the boat.
- 4). Cut out the appropriate mounting template below. Tape it on to the mounting surface such that the reference line (drawn above) is directly underneath the reference line marked on the template.
- 5). Drill indicated holes through the template to accommodate #8 oval head mounting screws.
- 6). Attach supply connections to the light, making sure to wire in accordance with both A.B.Y.C. Standard E-9* and U.S. Coast Guard Safety Standards for Boat Electrical Systems (33 CFR 183)*.



The supply leads are coded as follows:

- WHITE: Forward compartment (masthead light) positive supply lead.
- RED or GRAY: Aft compartment (when energized with the forward compartment: all-round light) positive supply lead.
- BLACK: Negative supply lead. (CAUTION: Negative lead connected to case. To avoid energizing case, observe polarity).

Electrical connections are to be made such that only the forward compartment (masthead light) is energized with the other running lights (sidelights, stern light, etc.) while underway. Both compartments are energized simultaneously by themselves to create the all-round (anchor) light. Be sure to use double-pole switches, otherwise feedback will cause all lights in the system to be energized at the wrong time. See wiring diagram.

- 7). Mount the light in accordance with the template. A plastic mounting insulator (is supplied).
- 8). Make sure the top of the light is vertical during operation (see illustration), the arrow on the top cover points ahead (not astern), and the reference marks are parallel to the fore-aft centerline of the boat.

WIRING DIAGRAM FOR COMBINATION MASTHEAD/ANCHOR LIGHTS



- Double pole, double throw switch (center off)
- One position illuminates running lights (masthead, side & stern)
- Other position illuminates anchor light (forward & aft compartments of combination masthead/anchor light)



AHEAD

NOTE: TOP OF LIGHT MUST BE VERTICAL DURING OPERATION

This is a 3/4" circle in order to scale internet printed templates

MOUNTING TEMPLATES

