



## Masthead Lights

### 3-mile (USCG 3nm) Certified

Use on Sail or Power Driven Vessels Under 20m (65.6 ft.) in Length

Material:	All Polymer	
Finish:	Black	
Dimensions:	Height: 7", Width: 4-1/8", Projection: 4-3/4"	
Screw Size:	#10	
Voltage:	12V LED or Incandescent (Bulb Included)	
<u>Masthead Light</u>	<u>Incandescent</u>	<u>LED</u>
Watts:	10 watts	5.6 watts
Amperage:	.83 amps	0.4 amps
<u>Spreader Light</u>		
Watts:	20 watt	2.2 watts
Amperage:	1.56 amps	0.18 amps

Features: Bottom light works as a Combination Spreader and Deck Illumination Light


### Combination Masthead/Deck Spreader Light



Fig. 0170BMD LED

Navigation Lights

Light Type	Retail Pkg.	Std. Pkg.
Incandescent	0170BMDDP1	0170BMD12V
LED	-----	0170BMD12L



LED Spreader Light

Fig. 0170BMD Incandescent



### 2-mile Certified A-16 for replacement use only

Use on Sail or Power Driven Vessels Under 12m (39.4 ft.) in Length

Material:	Brass or Stainless Steel Top, Polymer Base
Finish:	Chrome Plated or Polished
Dimensions:	O.D. Base: 2-3/8", Height: 1-5/8"
Screw Size:	#4
Contacts:	Gold Plated
Voltage:	12V (Bulb Included)
Wattage:	10 watts
Amperage:	.80 amps



Fig. 0964 Masthead

Finish	Retail Pkg.
Chrome Plated	0964DP0CHR
Polished SS	0964DP0STS



Fig. 0964 can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior to 11/1/03. Replace the bulbs provided with Cat. No. 0072DP1CLR 24-volt bulbs. Contact us for 12 or 24 volt applications on new construction.

### Spare Parts Information

**Fig. 0170 BMD:**  
Masthead Bulb: 0070DP1CLR.  
12V Halogen Bulb for Deck Spreader Light: 006812V20W.  
L.E.D.'s have no user serviceable parts



Fig. 0070DP1CLR

**Fig. 0964:**  
Lens (Open Top): 0281DPAWHT.  
Lens (Closed Top): 0295DPOWHT.  
Bulbs: 0071DPOCLR.  
Base with Socket Assembly: 0135.



Fig. 0071DPOCLR

Fig. 0295

Fig. 0281