



## Horizontal Mount Side Lights

### 2-mile (USCG 2nm) Certified

Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Zinc Alloy Top with Black or White Base,  
 Finish: Chrome Plated or White Powder Coated  
 Dimensions: Length: 3-1/4", Width: 2-1/4", Height: 1-1/2"  
 Screw Size: #6  
 Contacts: Gold Plated  
 Voltage: 12V (Bulb Included)  
 Wattage: 10 watts (each light)  
 Amperage: .80 amps (each light)



Fig. 0228  
Chrome



White

Navigation Lights

Finish	Retail Pkg.*	OEM Bulk Pkg.*
Chrome	0228DP0CHR	0228000CHR
White	0228DP0WHT	0228000WHT



\*Sold in pairs.

### 1-mile (USCG 1nm) Certified

Use on Sail or Power Driven Vessels Under 12m (39.4 ft.) in Length

Material: Polymer  
 Finish: Black  
 Dimensions: Base: 1-1/8" x 3", Height: 1-7/8"  
 Mount: Fig. 1601 - Normal "Base-Down"  
 Fig. 1602 - Inverted "Base-Up"  
 Screw Size: #8  
 Voltage: 12V (Bulb Included)  
 Wattage: 10 watts (each light)  
 Amperage: .80 amps (each light)  
 Use: Great for Pontoon Boats

Fig. 1601



Fig. 1602

Mount	Retail Pkg.*	OEM Bulk Pkg.*
Base Down	1601DP0BLK	1601000BLK
Base Up	1602DP0BLK	1602000BLK



\*Sold in pairs.

Note: The above lights can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior to 11/1/03. Replace the bulbs provided with Cat. No. 0072DP1CLR 24-volt bulbs. Contact us for 24-volt applications on new construction.

### Spare Parts Information

#### Fig. 0228:

Green Lens: 0228DPGLNS.  
 Red Lens: 0228DPRLNS.  
 Bulbs (2 per card): 0071DP0CLR.  
 Black Base w/Socket Assy: 022700099A.  
 White Base w/Socket Assy: 0227W0099A.



Fig. 0228



Fig. 0071DP0CLR

#### Figs 1601 & 1602:

Red Lens Only: 0298DPRLNS,  
 Green Lens Only: 0298DPGLNS  
 Red Light Only: 1601R00BLK, 1602R00BLK  
 Green Light Only: 1601G00BLK, 1602G00BLK  
 Bulbs: 0071DP0CLR  
 Base w/Socket Assembly: 0139000BLK



Fig. 0298



Fig. 0071DP0CLR