

The above lights are designed for use on power driven vessels under 20 meters (65.6 ft.) in length operating on a nominal 12 volt system. In order to comply with '72 COLREGS and the U.S. Inland Rules, the following must be adhered to:

### ***MOUNTING INFORMATION***

Read all instructions before proceeding.

- 1). For proper light selection, positioning and configuration, refer to A.B.Y.C. Standard A-16\*, the '72 COLREGS\*, and the U.S. Inland Rules\*. These lights are supplied with 12 volt bulbs, (Cat. No. 0338DP2CLR - 12V, 9W)
- 2). These lights are designed to be mounted on a horizontal surface. Horizontal rotation of these lights is unimportant, as all-round lights have 360° horizontal arc of visibility
- 3). Cut out the template below. Tape it to the mounting surface.
- 4). Drill two holes through the template to accommodate #8 oval head mounting screws. Drill one 3/8 inch hole to accommodate the electrical supply wires.
- 5). Attach supply connections to the light, making sure to wire in accordance with both A.B.Y.C. Standard E-9\* and U.S. Coast Guard Safety Standards for Boat Electrical Systems (33 CFR 183)\*.
- 6). Mount the base in accordance with the template.
- 7). Make sure the light is vertical during operation, in order to assure compliance with the technical details of the regulations and employ the "Reduced Glare" feature of this optical system.

