



White All-Round Navigation Lights

2-mile (USCG 2nm) Certified

Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Polymer Top and Base with Frosted Lens and 3/4" aluminum tube
 Fig. 1638: Chrome Plated Zinc Alloy Base

Finish: Black

Screw Size: #8

Voltage: 12V (Bulb Included)

Wattage: 9 watts

Amperage: .69 amps

Features: 360° Reduced Glare Design

Fig. 1604: **Fixed Mount** - two pole lengths

Fold-Down Mts: Feature adjustable angle (0° to 180°) for poles less than 18" long, include adapters available for flat or "V" type 45° mounts and a notch for through base wiring.

Fig. 1634: **Horizontal Mount** - Folds down 90° in either direction opposite the plane of attachment plate of the mount.

Fig. 1637: **Vertical Mount** - Folds down 90° in either direction along the plane of attachment plate of the mount.

Fig. 1638: **Quick Adjust Lever** - Ideal for use on pontoon boat square rails or any flat mounting surface.

Fig. 1607: **For Tower/Arch Mounts** - Serves as 360° all-round navigation light in the up position for nighttime boating or while at anchor and a cockpit courtesy light in the down position while at the dock. Stores forward and out of the way for daytime skiing or boarding. Mounts on 7/8" diameter tubing.

0239 Head Style Coastal Series



Fig. 1637 Vertical Mt. (Shown)

Navigation Lights

Fixed & Folding Mount Options



Fig. 1634 Horizontal Mount



Fig. 1637 Vertical Mount



Fig. 1638 Quick Adjust Handle



Fig. 1607 Tower/Arch Folding Mt.



Fig. 1604 Fixed Mount



Base Mount	Height Overall	Base Dimensions	Retail Pkg.	OEM Bulk Pkg.
Fixed Mt.	7-3/8"	1" x 2-5/8"	1604DP0CHR	1604000CHR
Fixed Mt.	3-1/8"	1" x 2-5/8"	1604DP1CHR	1604001CHR
Folding Mt.				
Horizontal Mt.	14-3/4"	2" x 1-1/2"	1634DP0CHR	1634000CHR
Vertical Mt.	14-1/8"	2-1/4" x 5/8"	1637DP0CHR	1637000CHR
Quick Adjust	13-7/8"	2-1/4" x 5/8"	1638DP0CHR*	1638000CHR*
Tower Mt.				
Fixed Mt.	8"	2" x 1-1/2"	1607DP0CHR	1607000CHR

* Refers to Prop65 Warning

Diagram of Tower/Arch Mounted Light




Fig. 0338



Fig. 0239DP0BLK

