



# Rule-Mate™ Series

FULLY AUTOMATED BILGE PUMPS

**The Rule Mate series of Bilge pumps feature a solid state water sensing technology that eliminates the need for a separate float switch.**

When water enters the bilge and reaches a certain height (2-3/4 inches) a sensor turns the pump on. After the water is pumped out, another sensor shuts the pump off.

The sensor's unique "field effect" technology will only recognize water. If a 100% concentration of oil is detected the pump will not activate. This is not a zero discharge prevention system. The result is the most technically advanced bilge pump available in the marketplace.

Rule Mate II series are available in 500, 750 and 1100. Rule has been building bilge pumps for 30 years. The pumps are preferred by yachtsmen and commercial fishermen the world over.




## Features and Benefits

- All-in-one pump & switch - No float switch required
- Snap-off strainer for easy cleaning
- Pump turns on when water level rises & shuts off when water is removed
- Anti-Fouling Impeller
- Limited three year warranty



  
a xylem brand

# Rule-Mate Series FULLY AUTOMATED BILGE PUMPS

 <p>Rule-Mate Automated Bilge Pump</p>	<b>Each Pump Includes</b>	
	 <p>(1) Straight Hose Barb Fitting</p>	 <p>(1) 90° Angled Hose Barb Fitting</p>

## Bilge Pump Accessories Available from Rule



### Deluxe Smooth Bore PVC Ribbed Bilge Hose

Clear ribbed bilge hose. Smooth inside finish improves pump performance by 30%. Rigid helix provides excellent abrasion resistance. Available in 3/4" (19mm), 1-1/8" (29mm), 1-1/2" (38mm) I.D. hose in 100' (31m) lengths.



### 3-way Panel Lighted Rocker Switch

Controls all Rule-Mate models. The unit features a black plastic panel. It has a built-in fuse holder and an internally lighted rocker switch with three positions (automatic, off, or manual) with the Rule fail-safe spring return to "off" from "manual" position.

## Electromechanical Rule Mate I series are available in 1500 & 2000



RM1500



RM2000

GPH/ LPH	Model	Volts	Amps @ 12V	Amps @ 13.6V	Fuse Size	Fittings	Hose Dia.	UPC
500 (1890)	RM500A	12 DC	2.0 (12V)	2.2 (13.6V)	3	YES	3/4" (19mm)	042237-111067
500 (1890)	RM500A-24	24 DC	1.0 (24V)	1.1 (27.2V)	1.5	YES	3/4" (19mm)	042237-111074
750 (2839)	RM750A	12 DC	2.7 (12V)	3.1 (13.6V)	5	YES	3/4" (19mm)	042237-111081
750 (2839)	RM750A-24	24 DC	1.4 (24V)	1.6 (27.2V)	3	YES	3/4" (19mm)	042237-111098
1100 (4164)	RM1100A	12 DC	3.4 (12V)	4.0 (13.6V)	5	YES	1-1/8" (29mm)	042237-111104
1100 (4164)	RM1100A-24	24 DC	1.7 (24V)	2.0 (27.2V)	3	YES	1-1/8" (29mm)	042237-111111

Check out the collection of boat plumbing we offer.