

## Features

Power/Ground Cable Assy: - 6 ft equal length 8AWG solid darkk blue + 8AWG solid gray, ultra-flex fine strand, tinned OFC -BC-5W2 compliant, heat resistant to 105°C -UV-resistant treatment - braided nylon jacket (black) + heat shrink - (2) ring terminals, blue and black boots (installed on short end) - (1) in-line waterproof MANL fuse holder (installed on blue wire) Remote Wire Assy: - (3 ft) solid blue jacket -BC-5W2 compliant, heat resistant to 105°C -UV-resistant treatment - braided nylon jacket (black) + heat shrink - (1) 18-22AWG male disconnect, red (installed) Speaker Wire Assy: - (2) 4ft 16AWG solid gray, tinned OFC -BC-5W2 compliant, heat resistant to 105°C -UV-resistant treatment + braided nylon jacket (black) + heat shrink (installed, centered on wire) Accessories: - (1) 60A MANL Fuse - (1) 8AWG amp spade terminal, blue boot - (1) 8AWG amp spade terminal, black boot - (1) 18-22AWG remote butt connector, red - (1) 18-22AWG remote spade terminal, red - (1) 18-22AWG remote female disconnect, red (full insulation, clear vinyl or nylon) - (4) 14-16AWG speaker female disconnects, blue (full insulation, clear vinyl or nylon) - (4) 14-16AWG speaker spade terminals, blue - (10) 8" cable ties - (1) S3 Wrench - (1) S2 Wrench - instructions - (2) 47 Ohm, 1/2 Watt resistors (for motorcycle speakers) - (1) black heat shrink Packaging: - EFX blister

