

SOUNDSTREAM

CAR AUDIO PRODUCTS



R E S E R V E

2021

Floating Display Multimedia Source Unit

VRCPAA-106

IN-CAR ENTERTAINMENT SYSTEM w/ APPLE CARPLAY, ANDROID AUTO, SIRIUSXM-READY™ & SWIVELING HIGH DEFINITION 10.6" LCD



ENTERTAINMENT CENTER GENERAL INFORMATION

ISO 2-DIN CHASSIS INSTALLS IN MOST NEWER VEHICLES
 UNIVERSAL MOUNTING BRACKETS & HARDWARE INCLUDED
 APPLE CARPLAY WITH SIRI EYES FREE BUILT-IN (VRCPAA ONLY)
 ANDROID AUTO WITH GOOGLE ASSISTANT BUILT-IN (VRCPAA ONLY)
 SIRIUSXM-READY™ (VEHICLE TUNER AND SUBSCRIPTION REQUIRED) (VRCPAA ONLY)
 VERTICAL ADJUSTMENT MECHANISM FOR OPTIMUM VIEWING (VRCPAA-106)
 SMARTSENSE CLEAR GLASS CAPACITIVE TOUCHSCREEN
 BLUETOOTH 4.2 PHONE CALLING + A2DP AUDIO STREAMING
 10-BAND 14dB BOOST/CUT EQUALIZER & PRESET EQS
 ADVANCED FM/AM TUNER WITH RDBS DATA DISPLAY
 ACCEPTS OEM STEERING WHEEL CONTROL WIRING
 WIRELESS DIRECT SELECT REMOTE CONTROL INCLUDED
 REAR VIEW CAMERA INPUT w/ MANUAL & AUTO-TRIGGER
 FRONT CAMERA RCA INPUT w/ ON-SCREEN TRIGGER

SIRIUSXM SATELLITE RADIO READY (VRCPAA ONLY)

ONLY SIRIUSXM® BRINGS YOU MORE OF WHAT YOU LOVE TO LISTEN TO, ALL IN ONE PLACE. GET OVER 140 CHANNELS, INCLUDING COMMERCIAL FREE MUSIC PLUS THE BEST SPORTS, NEWS, TALK, COMEDY AND ENTERTAINMENT. WELCOME TO THE WORLD OF SATELLITE RADIO. A SIRIUSXM VEHICLE TUNER AND SUBSCRIPTION ARE REQUIRED. FOR MORE INFORMATION, VISIT WWW.SIRIUSXM.COM. VEHICLE TUNER AND SUBSCRIPTION REQUIRED. SIRIUS, XM AND ALL RELATED MARKS AND LOGOS ARE TRADEMARKS OF SIRIUS XM RADIO INC. ALL RIGHTS RESERVED.

TURN-BY-TURN GPS NAVIGATION (VRN ONLY)

TURN-BY-TURN GPS NAVIGATION w/ ROUTE DATABASE, POWERED BY IGO USA MAP & +17 MILLION POINT-OF-INTEREST DATABASE INCLUDED
 MAP & POI UPDATES AVAILABLE FROM NAVIEXTRAS.COM
 CHOOSE DESTINATION BY ADDRESS, POI, OR GPS LOCATION
 ON-SCREEN & AUDIBLE TEXT-TO-SPEECH COMMANDS
 HIGHWAY & MAJOR ROAD LANE DEPARTURE GUIDANCE

R E S E R V E



Multimedia In-Dash Source Units

VRCPAA-7D

IN-CAR ENTERTAINMENT SYSTEM w/ APPLE CARPLAY, ANDROID AUTO, SIRIUSXM-READY™ & 7" LCD



Works with
Apple CarPlay

androidauto



VRN-7HB

GPS NAVIGATION + PHONELINK FOR ANDROID



VR-7HB

DVD AUDIO/VIDEO + PHONELINK FOR ANDROID

PHONELINK FOR ANDROID (VRN & VR ONLY)

ENABLED SMART DEVICE MIRRORS DISPLAY TO HEAD UNIT
2-WAY COMMUNICATION ENABLES MOBILE DEVICE CONTROL
STAY CONNECTED WITHOUT HANDLING DISTRACTING DEVICES
RETAINS USE OF SMART DEVICE'S VOICE RECOGNITION SERVICE
CONNECTION REQUIRES ORIGINAL USB CHARGING CABLE
2A USB CHARGING MAINTAINS BATTERY LIFE (FRONT)

DYNAMIC USER INTERFACE w/ SMARTSENSE TOUCH

HD 10.6" 1,024x600 TFT LCD w/ ADJUSTABLE BACKLIGHT (VRCPAA-106)
HD 7" 800x480 TFT-LCD w/ ADJUSTABLE BACKLIGHT (7D & 7HB)
PINPOINT ACCURACY CAPACITIVE TOUCHSCREEN
LOW REFLECTION INDUSTRIAL GRADE GLASS TOP PANEL
LARGE FORMAT USER INTERFACE REDUCES DISTRACTION
7 COLOR SELECTABLE TOUCH KEY ILLUMINATION

BLUETOOTH V4.2 HANDS-FREE WIRELESS CONNECTIVITY

HANDS-FREE PROFILE DIALS & RECEIVES CALLS & DISPLAYS CALL LOGS
PHONE BOOK ACCESS PROFILE DISPLAYS CALLER ID INFO & CONTACTS
AUDIO/VIDEO REMOTE CONTROL PROFILE ENABLES PLAYBACK CONTROLS
ADVANCED AUDIO DISTRIBUTION PROFILE STREAMS AUDIO WIRELESSLY

USB AUDIO/VIDEO PLAYBACK

VIDEO & AUDIO PLAYBACK FROM DVD, DVDR, CD, & CDR DISCS
MP3 & WMA AUDIO FILES FROM 64GB USB OR MICRO/TF SD
MP4, & H264 VIDEO FILES FROM 64GB USB OR MICRO/TF SD
ID3 MP3 TAG READING FOR TRACK & ARTIST INFORMATION

AUDIO/VIDEO CONFIGURATIONS

4CH. 300W MAX CLASS A/B FULL RANGE SPEAKER AMPLIFIER BUILT-IN
AUX AUDIO (3.5MM) INPUT FOR EXTERNAL DEVICES ON FRONT PANEL
5CH 4V PREAMP RCA OUTPUTS; FRONT + REAR + SUBWOOFER
AUDIO/VIDEO RCA INPUT & VIDEO OUTPUT FOR AUXILIARY DEVICES



SOUNDSTREAM

RESERVE SUBWOOFERS

In recent years, our subwoofers have evolved to meet various performance and placement goals, keeping your, the Soundstream fanatic, suggestions in mind. New for 2020, we introduce Reserve subwoofers, available exclusively to our Soundstream Reserve dealers. Premium materials & performance characteristics include over saturated 12mm top plate and t-yoke, high density poly-ether foam surround, & a massive 1,000w 3" voice coil. High density Spruce pulp cone and double poly-cotton blend suspension hold everything together. These behemoths are not for the faint-hearted....



- OVERCOMPENSATING MOTOR STRUCTURE FOR INCREASED MAGNETIC STRENGTH
- 12MM T-YOKE & TOP PLATE IMPROVE LOW FREQUENCY DYNAMICS
- VENTED T-YOKE & FRAME REDUCES VOICE COIL HEAT BUILD-UP
- NON-MAGNETIC NON-RESONATE DIE-CAST ALUMINUM FRAME
- 3" 4-LAYER VOICE COIL W/ DIRECT CONNECT WIRE INCREASES POWER HANDLING
- HIGH-TEMPERATURE TOLERANCE ADHESIVES RESIST THERMAL FAILURE
- NON-TRANSFER SPRUCE PULP CONE W/ UV & CHEMICAL PROTECTION
- STITCHED AND GLUED SURROUND/CONE JOINTS FOR STRONGEST BONDING
- EXTENDED EXCURSION POLY-ETHER FOAM SURROUND W/ UV & CHEMICAL PROTECTION
- DUAL POLY-COTTON SUSPENSION DAMPEN VIOLENT ACCELERATIONS
- 1-PC GASKET/TRIM RING W/ CONCEALED MOUNTING HOLES INCLUDED

RESERVE SUBWOOFER	RSW.122	RSW.152
MAX POWER (WATTS)	1,800W	2,600W
RMS POWER (WATTS)	900W	1,300W
EFFICIENCY (1W/1M dB)	83.5dB	88dB
VOICE COIL CONFIGURATION	3" DVC 2Ω	3" DVC 2Ω
MOUNTING DEPTH	6.25"	9.25"
OPTIMUM SEALED BOX	0.75FT ³	2.00FT ³
OPTIMUM PORTED BOX	1.25FT ³	4.00FT ³

REFERENCE SUBWOOFERS

- THIRD GENERATION SOUNDSTREAM REFERENCE FRAME
- OVERSATURATED MOTOR STRUCTURE FOR INCREASED MAGNETIC STRENGTH
- 12MM VENTED T-YOKE & TOP PLATE IMPROVE LOW FREQUENCY DYNAMICS
- 317OZ DOUBLE STACK MAGNET, T-YOKE & TOP PLATE
- 2.5" 4-LAYER VOICE COIL W/ LARGE GAUGE WIRE INCREASES POWER HANDLING
- HIGH-TEMPERATURE TOLERANCE ADHESIVES RESIST THERMAL FAILURE
- INVERTED ROLL POLYETHER FOAM SURROUND W/ UV & CHEMICAL PROTECTION
- OVERSIZED CONCAVE IMPP PRIMARY CONE INCREASES EFFECTIVE SURFACE AREA
- NON-TRANSFER SPRUCE PULP CONE W/ UV & CHEMICAL PROTECTION
- ACOUSTIC CANCELING POLYVINYL CHLORIDE GASKET & TRIM RING
- NICKEL PLATED 12GA SPRING-LOADED COMPRESSION WIRE TERMINALS
- STITCHED VOICE COIL LEADS PREVENT POTENTIAL DAMAGE
- DUAL POLY-COTTON SUSPENSION DAMPEN VIOLENT ACCELERATIONS



REFERENCE R5	R5.122	R5.124
MAX POWER (WATTS)	2,000W	
RMS POWER (WATTS)	1,000W	
EFFICIENCY (1W/1M)	85.00dB	
VOICE COIL CONFIGURATION	2.50" DVC 2Ω	2.50" DVC 4Ω
MOUNTING DEPTH	7.00"	
OPTIMUM SEALED FT ³	1.00FT ³	
OPTIMUM PORTED FT ³	2.00FT ³	

RESERVE SPEAKERS

When it comes to making affordable speakers worth listening too, you must think outside of the box. Reserve speakers uses non-traditional materials to be innovative, while maintaining great sound. Everyone agrees paper sounds better, right? Taking your listening experience to the next level, Reserve speakers use pulp fiber cones reinforced with mica, a crystalline structured additive. Mica increases the cones dimensional stability, stiffness, and strength, suppressing cone radiated distortions. Tweeters of Reserve speakers are made with a woven poly-nylon synthetic material formed into a dome shape. This textile material generates mild upper frequency tones, while the contoured dome widens the sound wave dispersion patterns.



RS.42



RS.52



RS.65



RS.57



RS.69

NATURAL PULP FIBER CONE W/ MICA CRYSTALLINE ADDITIVE
 3/4" WOVEN POLY-NYLON HEMISPHERICAL DOME TWEETER
 INTEGRATED PASSIVE 6dB HIGH PASS CROSSOVER FILTER
 REAR-ATTACHED SURROUND INCREASES EFFECTIVE CONE AREA
 POLY-COTTON DAMPER W/ WOVEN BRAIDED TINSEL LEADS
 1" O.F.C. COPPER VOICE COIL ON ALUMINUM FORMER
 POWDER COATED MESH STEEL GRILL INCLUDED (SELECT SIZES)

RESERVE SPEAKERS	RS.69	RS.65	RS.57	RS.52	RS.42
Size and Configuration	6"x9" 2-way	6.5" 2-way	5"x7" 2-way	5.25" 2-way	4" 2-way
RMS Power (watts)	80w	60w	60w	50w	40w
Resonant Frequency	47.3Hz	64Hz	63Hz	97Hz	115Hz
Efficiency (1w/1m dB)	88.9	86.6	87.5	85.5	84.3
Mounting Depth	3.00"	2.25"	2.25"	2.00"	2.00"

SOUNDSTREAM

Digital Pre-Amp Amplifiers

DIGITAL PRE-AMP AMPLIFIERS OFFER INNOVATIVE KOREAN MADE APPROACH TO TRADITIONAL SOUND PROCESSING. DPA AMPS INCLUDE A DIGITAL SIGNAL PROCESSING INTEGRATED CIRCUIT MODULE WHICH OPENS THE DOOR FOR PRECISE TUNING OF CROSSOVERS & GAIN SETTINGS. KEEPING THE USER IN MIND, ALL FUNCTIONS ARE CONTROLLED BY TOP SURFACE MOUNTED KEYS, NEEDING ONLY A FINGERS PRESS & KNOB TURN. SELECTED CROSSOVER FREQUENCIES AND GAIN LEVELS ARE DISPLAYED ON AN ADJACENT LCD, SHOWING OPERATING VOLTAGE & TEMPERATURE WHILE IDLE. FULL FEATURED PRE-AMP OPTIONS, INCLUDING BAND-PASS & SUBSONIC CROSSOVERS, BASS BOOST, & EVEN VARIABLE PHASING MAKE DPA AMPS A GO-TO FOR ANY ENTHUSIAST.



R
E
S
E
R
V
E

HIGH EFFICIENCY CLASS D FULL RANGE & MONOBLOCK AMPLIFIERS
 HYBRID ALUMINUM ALLOY HEATSINK FOR OPTIMUM DISSIPATION
 2-OHM STEREO & 4-OHM BRIDGED IMPEDANCE STABILITY (DPA4 & DPA5)
 MOSFET POWER SUPPLY W/ AUDIOPHILE GRADE IR™ TRANSISTORS
 MILITARY GRADE SMT PCB MAINTAINS DYNAMIC PERFORMANCE
 DIRECT SHORT, THERMAL, & OVERLOAD CIRCUITS PROTECT AMPLIFIER
 ADVANCED DIGITAL PRE-AMP PROCESSING FOR PRECISE TUNING

200MV-6V HIGH/SPEAKER LEVEL OR LOW LEVEL/RCA INPUT
 QUICK DISCONNECT HIGH L& LOW LEVEL WIRE HARNESSES INCLUDED
 QUICK DISCONNECT SPEAKER LEVEL OUTPUT HARNESSES INCLUDED
 LOW-LEVEL THRU-PASS OUTPUT TO DAISY CHAIN MULTIPLE AMPLIFIERS
 VARIABLE 12dB HIGH, LOW, BAND-PASS, & SUBSONIC CROSSOVERS
 VARIABLE 180° PHASE SHIFT TO MATCH POLARITY OF SYSTEM SPEAKERS
 DASH MOUNT GAIN CONTROL MODULE INCLUDED (DPA1 & DPA5)

DIGITAL PRE-AMP SERIES	DPA4.1600D	DPA5.2000D	DPA1.2000D
MAX POWER	1,600W	2,000W	2,000W
RMS POWER 4Ω	80 x 4	75 x 4 + 200 x 1	250 x 1
RMS POWER 2Ω	160 x 4	125 x 4 + 400 x 1	400 x 1
RMS POWER 4Ω BRIDGED	320 x 2	250 x 2 + 400 x 1 (2Ω)	-
RMS POWER 1Ω BRIDGED	-	-	700 X 1
REMOTE GAIN CONTROL	-	INCLUDED	INCLUDED
DIMENSIONS (4"W x 1.75"H)	9.00"	11.5"	9.00"



Reserve Micro Amplifiers

DON'T LET THESE LITTLE MONSTERS FOOL YOU. THE LATEST AND GREATEST OF CLASS D FULL RANGE TECHNOLOGY ALLOWS US TO PACK 10 LBS OF KICK YOUR ASS IN A 2-LB CHASSIS. ONCE REGARDED AS "DIRTY POWER", CLASS D'S STABLE PERFORMANCE, THANKS TO HIGH POWER CAPABILITY, MAXIMUM EFFICIENCIES, AND LOW TOLERANCE COMPONENTS, RIVALS TRADITIONAL FULL RANGE APPLICATIONS. MINIMAL POWER REQUIREMENTS, ULTRA MICRO FOOTPRINT, UNBELIEVABLE SOUND QUALITY, AND EASY INSTALL MAKES RESERVE MICRO AMPLIFIERS GREAT FOR ANY CAR, MOTORCYCLE, BOAT, OR OFF-ROAD VEHICLE.



RESERVE MICRO AMPLIFIERS	RSM4.1200D	RSM1.2000D	RSM1.4000D
MAX POWER	1,200W	2,000W	4,000W
RMS POWER 4Ω	75 x 4	360 x 1	600 x 1
RMS POWER 2Ω	110 x 4	480 x 1	850 x 1
RMS POWER 4Ω BRIDGED	220 x 2	-	-
RMS POWER 1Ω BRIDGED	-	600 x 1	1,200 x 1
REMOTE GAIN CONTROL	-	INCLUDED	INCLUDED
DIMENSIONS (3.75"W x 1.75"H)	6.75"	7.50"	9.25"

HIGH EFFICIENCY CLASS D FULL RANGE & MONOBLOCK AMPLIFIERS
 HYBRID ALUMINUM ALLOY HEATSINK FOR OPTIMUM DISSIPATION
 2-OHM STEREO & 4-OHM BRIDGED FULL RANGE OPERATION
 1-OHM MINIMUM IMPEDANCE MONOBLOCK OPERATION
 MOSFET POWER SUPPLY W/ AUDIOPHILE GRADE IR™ TRANSISTORS
 MILITARY GRADE SMT PCB MAINTAINS DYNAMIC PERFORMANCE

DIRECT SHORT, THERMAL, & OVERLOAD CIRCUITS PROTECT AMPLIFIER
 200MV-6V HIGH LEVEL OR LOW LEVEL RCA INPUT
 DIRECT CONNECT POWER AND SPEAKER OUTPUT TERMINALS
 VARIABLE 12DB HIGH PASS, LOW PASS, & SUBSONIC CROSSOVERS
 12DB BASS BOOST INCREASES LOW OCTAVE HARMONICS (RSM1)
 DASH MOUNT GAIN CONTROL MODULE INCLUDED (RSM1)

SOUNDSTREAM

RESERVE Amplifiers

RESERVE AMPLIFIERS ARE THE NEXT STEP IN PERFORMANCE AND VALUE. TAKING ADVANTAGE OF OUR TRIED AND TRUE CLASS A/B FULL RANGE AND IMPROVED EFFICIENCY CLASS D MONOBLOCK PLATFORMS, RESERVE AMPLIFIERS CONTINUE DOWN THE ROAD OF RELIABILITY AND LONGEVITY YOU KNOW WELL. SATIN SILVER CHASSIS, ENGRAVING, AND ACCENTS TEETERING ON THE EDGES BRING A HIGH END APPEAL TO TRADITIONAL PERFORMANCE.



CLASS A/B FULL RANGE & CLASS D MONOBLOCK AMPLIFIERS
 2-OHM STEREO & 4-OHM BRIDGED FULL RANGE OPERATION
 1-OHM STABLE MONOBLOCK OPERATION FOR MAX POWER
 MILITARY GRADE PCB w/ PWM MOSFET POWER SUPPLY
 DIRECT SHORT, THERMAL, & OVERLOAD CIRCUIT PROTECTION
 HIGH/SPEAKER LEVEL & LOW LEVEL/RCA INPUT
 200MV-6V LOW LEVEL RCA INPUT

PRE-AMP LOW-LEVEL RCA OUTPUTS (SELECT MODELS)
 4G POWER WIRE & 8G SPEAKER WIRE OUTPUTS
 VARIABLE 12DB HIGH & LOW PASS CROSSOVERS
 12DB BASS BOOST INCREASES LOW OCTAVE HARMONICS
 1800 PHASE SHIFT IMPROVES LOW OCTAVE DYNAMICS (MONOBLOCK)
 DASH MOUNT REMOTE CONTROL INCLUDED (SELECT MODELS)

RESERVE AMPLIFIERS	RS2.1200	RS4.1200	RS4.2000	RS5.4500D	RS1.5000D	RS1.8000D
MAX POWER	1,200W	1,200W	2,000W	4,500W	5,000W	8,000W
RMS POWER 4Ω	150 × 2	75 × 4	150 × 4	100 × 4 + 500 × 1	800 × 1	1,200 × 1
RMS POWER 2Ω	220 × 2	110 × 4	220 × 4	160 × 4 + 750 × 1	1,200 × 1	1,700 × 1
RMS POWER 4Ω BRIDGED	440 × 1	220 × 2	440 × 2	320 × 2 + 1,000 × 1 (1Ω)	-	-
RMS POWER 1Ω	-	-	-	-	1,700 × 1	3,000 × 1
REMOTE GAIN CONTROL	-	-	-	INCLUDED	INCLUDED	INCLUDED
DIMENSIONS (8.25"W X 2"H)	10.75"	10.75"	13.00"	13.50"	11.75"	15.75"

SOUNDSTREAM