

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Form:** Mixture

**Product Name:** Startron Enzyme Fuel Treatment - Small Engine Formula - Gas

**Product Code:** 143XX

### Intended Use of the Product

**Use Of The Substance/Mixture:** Fuel Additive.

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Substance or Mixture

#### GHS-US/CA Classification

Skin Irrit. 2                    H315

STOT SE 3                    H336

Asp. Tox. 1                    H304

Full text of hazard classes and H-statements : see section 16

### Label Elements

#### GHS-US/CA Labeling

#### Hazard Pictograms (GHS-US/CA)



#### Signal Word (GHS-US/CA)

: Danger

#### Hazard Statements (GHS-US/CA)

: H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H336 - May cause drowsiness or dizziness.

#### Precautionary Statements (GHS-US/CA)

: P261 - Avoid breathing vapors, mist, or spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 - Call a POISON CENTER or doctor if you feel unwell.  
P321 - Specific treatment (see section 4 on this SDS).  
P331 - Do NOT induce vomiting.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national,

# Startron Enzyme Fuel Treatment - Small Engine Formula - Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

territorial, provincial, and international regulations.

### Other Hazards

Aquatic Acute 3 H402

Aquatic Chronic 3 H412

H402 - Harmful to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

P273 - Avoid release to the environment.

This material or its emissions may defat skin, cause contact dermatitis, or aggravate existing skin disease - may cause skin dryness or cracking. Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

| Name                                      | Product Identifier  | % *     | GHS Ingredient Classification   |
|---|---------------------|---------|---|
| Petroleum distillates, hydrotreated light | (CAS No) 64742-47-8 | 90 - 95 | Asp. Tox. 1, H304   |
| Kerosine, petroleum                       | (CAS No) 8008-20-6  | 1 - 10  | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401<br>Aquatic Chronic 2, H411 |
| Kerosine, petroleum, hydrodesulfurized    | (CAS No) 64742-81-0 | 1 - 10  | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>Aquatic Acute 3, H402<br>Aquatic Chronic 2, H411                      |

Full text of H-phrases: see section 16

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

## SECTION 4: FIRST AID MEASURES

### Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

### Most Important Symptoms and Effects Both Acute and Delayed

**General:** Causes skin irritation. Vapors may cause drowsiness and dizziness. May be fatal if swallowed and enters airways.

**Inhalation:** May cause drowsiness or dizziness. Prolonged exposure may cause irritation.

**Skin Contact:** Causes skin irritation. Redness, pain, swelling, itching, burning, dryness, and dermatitis. Repeated or prolonged skin contact may cause dermatitis and defatting.

**Eye Contact:** May cause slight irritation to eyes.

**Ingestion:** Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury. The major health threat of ingestion occurs from the danger of aspiration (breathing) of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure and even death.

**Chronic Symptoms:** None known.

# Startron Enzyme Fuel Treatment - Small Engine Formula - Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### **Indication of Any Immediate Medical Attention and Special Treatment Needed**

Any material aspirated during vomiting may cause lung injury. Avoid emesis. If stomach contents must be evacuated use method least likely to result in aspiration. If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## **SECTION 5: FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

**Suitable Extinguishing Media:** Water spray, dry chemical, foam, carbon dioxide.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### **Special Hazards Arising From the Substance or Mixture**

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### **Advice for Firefighters**

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. Remove containers from fire area if this can be done without risk. Do not breathe fumes from fires or vapors from decomposition.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Thermal decomposition generates: Carbon oxides (CO, CO<sub>2</sub>). Hydrocarbons. Nitrogen oxides.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

### **Reference to Other Sections**

Refer to Section 9 for flammability properties.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** Use only outdoors or in a well-ventilated area. Avoid breathing (vapor, mist, spray). Avoid all contact with skin, eyes, or clothing.

#### **For Non-Emergency Personnel**

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Stop leak if safe to do so. Evacuate unnecessary personnel.

#### **For Emergency Personnel**

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### **Environmental Precautions**

Prevent entry to sewers and public waters. Avoid release to the environment.

### **Methods and Materials for Containment and Cleaning Up**

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Ventilate area. Absorb and/or contain spill with inert material. Transfer spilled material to a suitable container for disposal. If spilled directly onto the ground, remove sufficient soil to ensure material is fully recovered. Contact competent authorities after a spill.

### **Reference to Other Sections**

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## **SECTION 7: HANDLING AND STORAGE**

### **Precautions for Safe Handling**

**Additional Hazards When Processed:** Repeated or prolonged skin contact may cause dermatitis and defatting.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, and spray.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### **Conditions for Safe Storage, Including Any Incompatibilities**

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up.

# Startron Enzyme Fuel Treatment - Small Engine Formula - Gas

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

## Specific End Use(s)

Fuel Additive.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

| <b>Kerosine, petroleum (8008-20-6)</b>                     |                                      |  |
|--|--------------------------------------|--|
| <b>USA ACGIH</b>   | ACGIH TWA (mg/m <sup>3</sup> )       | 200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures-total hydrocarbon vapor)               |
| <b>USA ACGIH</b>   | ACGIH chemical category              | Skin - potential significant contribution to overall exposure by the cutaneous route, Confirmed Animal Carcinogen with Unknown Relevance to Humans |
| <b>USA NIOSH</b>   | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 100 mg/m <sup>3</sup>  |
| <b>Alberta</b>   | OEL TWA (mg/m <sup>3</sup> )         | 200 mg/m <sup>3</sup>  |
| <b>British Columbia</b>                                    | OEL TWA (mg/m <sup>3</sup> )         | 200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures)                                       |
| <b>Manitoba</b>  | OEL TWA (mg/m <sup>3</sup> )         | 200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures-total Hydrocarbon vapor)               |
| <b>Newfoundland &amp; Labrador</b>                         | OEL TWA (mg/m <sup>3</sup> )         | 200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures-total Hydrocarbon vapor)               |
| <b>Nova Scotia</b>   | OEL TWA (mg/m <sup>3</sup> )         | 200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures-total Hydrocarbon vapor)               |
| <b>Northwest Territories</b>                               | OEL STEL (mg/m <sup>3</sup> )        | 250 mg/m <sup>3</sup>  |
| <b>Northwest Territories</b>                               | OEL TWA (mg/m <sup>3</sup> )         | 200 mg/m <sup>3</sup>  |
| <b>Ontario</b>   | OEL TWA (mg/m <sup>3</sup> )         | 200 mg/m <sup>3</sup> (restricted to conditions where there is negligible aerosol exposure)  |
| <b>Prince Edward Island</b>                                | OEL TWA (mg/m <sup>3</sup> )         | 200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures-total Hydrocarbon vapor)               |
| <b>Saskatchewan</b>  | OEL STEL (mg/m <sup>3</sup> )        | 250 mg/m <sup>3</sup>  |
| <b>Saskatchewan</b>  | OEL TWA (mg/m <sup>3</sup> )         | 200 mg/m <sup>3</sup>  |
| <b>Kerosine, petroleum, hydrodesulfurized (64742-81-0)</b> |                                      |  |
| <b>USA ACGIH</b>   | ACGIH TWA (mg/m <sup>3</sup> )       | 200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures-total hydrocarbon vapor)               |
| <b>USA ACGIH</b>   | ACGIH chemical category              | Skin - potential significant contribution to overall exposure by the cutaneous route, Confirmed Animal Carcinogen with Unknown Relevance to Humans |
| <b>Alberta</b>   | OEL TWA (mg/m <sup>3</sup> )         | 200 mg/m <sup>3</sup>  |
| <b>Manitoba</b>  | OEL TWA (mg/m <sup>3</sup> )         | 200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures-total Hydrocarbon vapor)               |
| <b>Newfoundland &amp; Labrador</b>                         | OEL TWA (mg/m <sup>3</sup> )         | 200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures-total Hydrocarbon vapor)               |
| <b>Nova Scotia</b>   | OEL TWA (mg/m <sup>3</sup> )         | 200 mg/m <sup>3</sup> (application restricted to conditions in which   |

# Startron Enzyme Fuel Treatment - Small Engine Formula - Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

|   |                               |  |
|---|-------------------------------|--|
|   |                               | there are negligible aerosol exposures-total Hydrocarbon vapor)  |
| <b>Northwest Territories</b>                                  | OEL STEL (mg/m <sup>3</sup> ) | 250 mg/m <sup>3</sup>  |
| <b>Northwest Territories</b>                                  | OEL TWA (mg/m <sup>3</sup> )  | 200 mg/m <sup>3</sup>  |
| <b>Ontario</b>  | OEL TWA (mg/m <sup>3</sup> )  | 200 mg/m <sup>3</sup> (restricted to conditions where there is negligible aerosol exposure)  |
| <b>Prince Edward Island</b>                                   | OEL TWA (mg/m <sup>3</sup> )  | 200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures-total Hydrocarbon vapor) |
| <b>Saskatchewan</b>   | OEL STEL (mg/m <sup>3</sup> ) | 250 mg/m <sup>3</sup>  |
| <b>Saskatchewan</b>   | OEL TWA (mg/m <sup>3</sup> )  | 200 mg/m <sup>3</sup>  |
| <b>Petroleum distillates, hydrotreated light (64742-47-8)</b> |                               |  |
| <b>British Columbia</b>                                       | OEL TWA (mg/m <sup>3</sup> )  | 200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures)                         |

### Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

**Materials for Protective Clothing:** Gloves. Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear protective gloves.

**Eye Protection:** Safety glasses with side shields, or goggles, are recommended.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment.

**Environmental Exposure Controls:** Avoid release to the environment.

**Other Information:** When using, do not eat, drink or smoke

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

|                                       |                     |
|---------------------------------------|---------------------|
| <b>Physical State</b>                 | : Liquid            |
| <b>Appearance</b>                     | : Clear             |
| <b>Odor</b>                           | : Solvent           |
| <b>Odor Threshold</b>                 | : Not available     |
| <b>pH</b>                             | : Not available     |
| <b>Evaporation Rate</b>               | : Not available     |
| <b>Melting Point</b>                  | : -42 °C (-43.6 °F) |
| <b>Freezing Point</b>                 | : Not available     |
| <b>Boiling Point</b>                  | : Not available     |
| <b>Flash Point</b>                    | : 94 °C (201.2 °F)  |
| <b>Auto-ignition Temperature</b>      | : Not available     |
| <b>Decomposition Temperature</b>      | : Not available     |
| <b>Flammability (solid, gas)</b>      | : Not available     |
| <b>Lower Flammable Limit</b>          | : Not available     |
| <b>Upper Flammable Limit</b>          | : Not available     |
| <b>Vapor Pressure</b>                 | : Not available     |
| <b>Relative Vapor Density at 20°C</b> | : Not available     |

# Startron Enzyme Fuel Treatment - Small Engine Formula - Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

|  |                 |
|--|-----------------|
| Relative Density                       | : Not available |
| Specific Gravity                       | : Not available |
| Solubility                             | : Not available |
| Partition Coefficient: N-Octanol/Water | : Not available |
| Viscosity                              | : Not available |
| Viscosity, Kinematic                   | : < 7 cSt       |

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Hazardous reactions will not occur under normal conditions.

**Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

**Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects - Product

**Acute Toxicity (Oral):** Not classified

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation.

**Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness.

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** May cause drowsiness or dizziness. Prolonged exposure may cause irritation.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation. Redness, pain, swelling, itching, burning, dryness, and dermatitis. Repeated or prolonged skin contact may cause dermatitis and defatting.

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury. The major health threat of ingestion occurs from the danger of aspiration (breathing) of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure and even death.

**Chronic Symptoms:** None known.

### Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

| Kerosine, petroleum (8008-20-6)                        |                |
|--|----------------|
| LD50 Oral Rat  | > 5000 mg/kg   |
| LD50 Dermal Rabbit                                     | > 2000 mg/kg   |
| LC50 Inhalation Rat                                    | > 5.28 mg/l/4h |
| Kerosine, petroleum, hydrodesulfurized (64742-81-0)    |                |
| LD50 Oral Rat  | > 5000 mg/kg   |
| LD50 Dermal Rabbit                                     | > 2000 mg/kg   |
| LC50 Inhalation Rat                                    | > 5.2 mg/l/4h  |
| Petroleum distillates, hydrotreated light (64742-47-8) |                |
| LD50 Oral Rat  | > 5000 mg/kg   |
| LD50 Dermal Rabbit                                     | > 2000 mg/kg   |

# Startron Enzyme Fuel Treatment - Small Engine Formula - Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

|                     |               |
|---------------------|---------------|
| LC50 Inhalation Rat | > 5.2 mg/l/4h |
|---------------------|---------------|

## SECTION 12: ECOLOGICAL INFORMATION

### Toxicity

**Ecology - General:** Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

|  |  |
|--|--|
| <b>Kerosine, petroleum (8008-20-6)</b> |  |
| LC50 Fish 1                            | 2 (2 - 5) mg/kg (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static]) |
| NOEC Chronic Fish                      | 0.098 mg/l (PETROTOX, Klimmish score: 2)   |

|  |   |
|--|---|
| <b>Kerosine, petroleum, hydrodesulfurized (64742-81-0)</b> |   |
| LC50 Fish 1  | 45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1   | 4720 mg/l (Exposure time: 48 h - Species: Den-dronereides heteropoda)       |
| LC50 Fish 2  | 1740 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])     |

|   |   |
|---|---|
| <b>Petroleum distillates, hydrotreated light (64742-47-8)</b> |   |
| LC50 Fish 1   | 45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| LC50 Fish 2   | 2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])      |

### Persistence and Degradability

|  |   |
|--|---|
| <b>Startron Enzyme Fuel Treatment - Small Engine Formula - Gas</b> |   |
| Persistence and Degradability                                      | May cause long-term adverse effects in the environment. |

### Bioaccumulative Potential

|  |                  |
|--|------------------|
| <b>Startron Enzyme Fuel Treatment - Small Engine Formula - Gas</b> |                  |
| Bioaccumulative Potential  | Not established. |

|  |          |
|--|----------|
| <b>Kerosine, petroleum, hydrodesulfurized (64742-81-0)</b> |          |
| BCF Fish 1   | 61 - 159 |

|   |          |
|---|----------|
| <b>Petroleum distillates, hydrotreated light (64742-47-8)</b> |          |
| BCF Fish 1  | 61 - 159 |

**Mobility in Soil** Not available

### Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Additional Information:** Container may remain hazardous when empty. Continue to observe all precautions.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

**In Accordance with DOT** Not regulated for transport

Marine Pollutant: No

**In Accordance with IMDG** Not regulated for transport

**In Accordance with IATA** Not regulated for transport

**In Accordance with TDG** Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

|  |                                 |
|--|---------------------------------|
| <b>Startron Enzyme Fuel Treatment - Small Engine Formula - Gas</b> |                                 |
| SARA Section 311/312 Hazard Classes                                | Immediate (acute) health hazard |

|   |  |
|---|--|
| <b>Kerosine, petroleum (8008-20-6)</b>                                    |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |

|   |  |
|---|--|
| <b>Kerosine, petroleum, hydrodesulfurized (64742-81-0)</b>                |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |

|   |  |
|---|--|
| <b>Petroleum distillates, hydrotreated light (64742-47-8)</b>             |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |

# Startron Enzyme Fuel Treatment - Small Engine Formula - Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### US State Regulations

#### Kerosine, petroleum (8008-20-6)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
 U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
 U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1  
 U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2  
 U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity  
 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1  
 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2  
 RTK - U.S. - Massachusetts - Right To Know List  
 U.S. - Minnesota - Chemicals of High Concern  
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
 U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances  
 U.S. - New Jersey - Environmental Hazardous Substances List  
 RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
 U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups  
 RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
 U.S. - Texas - Effects Screening Levels - Long Term  
 U.S. - Texas - Effects Screening Levels - Short Term

#### Kerosine, petroleum, hydrodesulfurized (64742-81-0)

U.S. - Texas - Effects Screening Levels - Long Term  
 U.S. - Texas - Effects Screening Levels - Short Term

#### Petroleum distillates, hydrotreated light (64742-47-8)

U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
 U.S. - Texas - Effects Screening Levels - Long Term  
 U.S. - Texas - Effects Screening Levels - Short Term

### Canadian Regulations

#### Kerosine, petroleum (8008-20-6)

Listed on the Canadian DSL (Domestic Substances List)

#### Kerosine, petroleum, hydrodesulfurized (64742-81-0)

Listed on the Canadian DSL (Domestic Substances List)

#### Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 07/05/2016

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR).

### GHS Full Text Phrases:

|                   |  |
|-------------------|--|
| Aquatic Acute 2   | Hazardous to the aquatic environment - Acute Hazard Category 2   |
| Aquatic Acute 3   | Hazardous to the aquatic environment - Acute Hazard Category 3   |
| Aquatic Chronic 2 | Hazardous to the aquatic environment - Chronic Hazard Category 2 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment - Chronic Hazard Category 3 |
| Asp. Tox. 1       | Aspiration hazard Category 1                                     |
| Flam. Liq. 3      | Flammable liquids Category 3                                     |
| Skin Irrit. 2     | Skin corrosion/irritation Category 2                             |
| STOT SE 3         | Specific target organ toxicity (single exposure) Category 3      |
| H226              | Flammable liquid and vapor                                       |



# Startron Enzyme Fuel Treatment - Small Engine Formula - Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

|      |   |
|------|---|
| H304 | May be fatal if swallowed and enters airways      |
| H315 | Causes skin irritation                            |
| H336 | May cause drowsiness or dizziness                 |
| H401 | Toxic to aquatic life                             |
| H402 | Harmful to aquatic life                           |
| H411 | Toxic to aquatic life with long lasting effects   |
| H412 | Harmful to aquatic life with long lasting effects |

### NFPA Health Hazard

: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

### NFPA Fire Hazard

: 1 - Must be preheated before ignition can occur.

### NFPA Reactivity Hazard

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

