

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 08/14/2014 Date of issue: 08/14/2014

SECTION 1: IDENTIFICATION

Product Identifier Product Name: Vinyl Brite Product Code: 803XX Intended Use of the Product

Cleaner

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US) Eye Dam. 1 H318 Label Elements GHS-US Labeling Hazard Pictograms (GHS-US)



Signal Word (GHS-US)	:	Danger
Hazard Statements (GHS-US)	:	H318 - Causes serious eye damage
Precautionary Statements (GHS-US)		P280 - Wear protective gloves, protective clothing, eye protection.
		P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove
		contact lenses, if present and easy to do. Continue rinsing.
		P310 - Immediately call a POISON CENTER or doctor/physician.
		P501 - Dispose of contents/container according to local, regional, national, territorial,

provincial, and international regulations.

Other Hazards

Other Hazards: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Aquatic Chronic 3

H412 - Harmful to aquatic life with long lasting effects

P273 - Avoid release to the environment

Unknown Acute Toxicity (GHS-US)

8 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

8 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

8 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture			
Name	Product identifier	% (w/w)	Classification (GHS-US)
Siloxanes and Silicones, di-Me	(CAS No) 63148-62-9	3 - 8	Eye Irrit. 2A, H319
2,6,8-Trimethyl-4-nonyl polyethylene glycol ether	(CAS No) 60828-78-6	2 - 6	Eye Dam. 1, H318
			Aquatic Chronic 3, H412

Version: 1.0

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Poly(oxy-1,2-ethanediyl), .alpha[3-[1,3,3,3-	(CAS No) 67674-67-3	1.4 - 2.6	Acute Tox. 4 (Inhalation:dust,mist), H332
tetramethyl-1-[(trimethylsilyl)oxy]disiloxanyl]			Eye Dam. 1, H318
propyl]omegahydroxy-			Aquatic Chronic 2, H411
Poly(oxy-1,2-ethanediyl), .alpha2-propenyl-	(CAS No) 27274-31-3	0.2 - 1	Skin Irrit. 2, H315
.omegahydroxy-			Eye Irrit. 2A, H319

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

Skin Contact: Remove contaminated clothing. Rinse affected area with water for at least 5 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye damage.

Inhalation: None expected under normal conditions of use.

Skin Contact: May cause mild skin irritation.

Eye Contact: Causes serious eye damage.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated or prolonged skin contact may cause dermatitis and defatting.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire. Application of water stream to hot product may cause frothing and increase fire intensity.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: None known.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Silicon oxides.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Avoid breathing (vapor, mist, spray).

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Stop leak if safe to do so.

Environmental Precautions

Prevent entry to sewers and public waters.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Specific End Use(s)

Cleaner.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Not applicable

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective clothing. Safety glasses. Gloves.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	:	Liquid
Appearance	:	White
Odor	:	Pleasant
Odor Threshold	:	Not available
рН	:	6.5
Relative Evaporation Rate (butylacetate=1)	:	Not available
Melting/Freezing Point	:	Not available
Boiling Point	:	100 °C (212 °F)
Flash Point	:	> 100 °C (212 °F)
Auto-ignition Temperature	:	Not available
Decomposition Temperature	:	Not available
Flammability (solid, gas)	:	Not available
Upper and Lower Flammable Limits	:	Not available
Vapor Pressure	:	Not available
Relative Vapor Density at 20 °C	:	Not available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative Density/Specific Gravity	:	1.01 (water = 1) at 20 °C (68 °F)
Solubility	:	Soluble in water.
Partition coefficient: n-octanol/water	:	Not available
Viscosity	:	Not available
Explosion Data – Sensitivity to Mechanical Impact	:	Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	:	Not expected to present an explosion hazard due to static discharge.
SECTION 10, STARILITY AND DEACTIVITY		

SECTION 10: STABILITY AND REACTIVITY

Reactivity: None known.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Silicon oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified (pH: 6.5)

Serious Eye Damage/Irritation: Causes serious eye damage. (pH: 6.5)

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: None expected under normal conditions of use.

Symptoms/Injuries After Skin Contact: May cause mild skin irritation.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated or prolonged skin contact may cause dermatitis and defatting.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

2,6,8-Trimethyl-4-nonyl polyethylene glycol ether (60828-78-6)

LD50 Dermal Rabbit 4780 µl/kg

 Poly(oxy-1,2-ethanediyl), .alpha.-[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy]disiloxanyl]propyl]-.omega.-hydroxy- (67674-67-3)

 ATE US (dust, mist)
 1.50 mg/l/4h

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life with long lasting effects.

Persistence and Degradability

Siloxanes and Silicones, di-Me (63148-62-9)

Persistence and Degradability	Not established.
-------------------------------	------------------

<u>Bioaccumulative Potent</u>ial

Siloxanes and Silicones, di-Me (63148-62-9)

Bioaccumulative Potential Not established.

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT Not regulated for transport

14.2 In Accordance with IMDG Not regulated for transport

14.3 In Accordance with IATA Not regulated for transport

14.4 In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Vinyl Brite

SARA Section 311/312 Hazard Classes

Siloxanes and Silicones, di-Me (63148-62-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2,6,8-Trimethyl-4-nonyl polyethylene glycol ether (60828-78-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Poly(oxy-1,2-ethanediyl), .alpha.-[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy]disiloxanyl]propyl]-.omega.-hydroxy- (67674-67-3) Listed on the United States TSCA (Toxic Substances Control Act) inventory

Immediate (acute) health hazard

Poly(oxy-1,2-ethanediyl), .alpha.-2-propenyl-.omega.-hydroxy- (27274-31-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations

Siloxanes and Silicones, di-Me (63148-62-9)

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

2,6,8-Trimethyl-4-nonyl polyethylene glycol ether (60828-78-6)

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Canadian Regulations

Vinyl Brite

WHMIS Classification

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects



Siloxanes and Silicones, di-Me (63148-62-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

2,6,8-Trimethyl-4-nonyl polyethylene glycol ether (60828-78-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Poly(oxy-1,2-ethanediyl), .alpha.-[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy]disiloxanyl]propyl]-.omega.-hydroxy- (67674-67-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Poly(oxy-1,2-ethanediyl), .alpha.-2-propenyl-.omega.-hydroxy- (27274-31-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

: This document has been prepared in accordance with the SDS requirements of the OSHA

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

: 08/14/2014

Other Information

Revision date

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

GHS F	ull Text Phrases:					
	Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4 Hazardous to the aquatic environment - Chronic Hazard Category 2				
	Aquatic Chronic 2					
	Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3 Serious eye damage/eye irritation Category 1				
	Eye Dam. 1					
	Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A				
	Skin Irrit. 2	Skin corrosion/irritation Category 2				
	H315	Causes skin irritation Causes serious eye damage				
	H318					
	H319	Causes serious eye irritation				
	H332	Harmful if inhaled				
	H411	Toxic to aquatic life with long lasting effects				
	H412	Harmful to aquatic life with long lasting effects				
NFPA Health Hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.						
NFPA	Fire Hazard : 0 - Materials that will					
NFPA	Reactivity : 0 - Normally stable, e water.	ven under fire exposure conditions, and are not reactive with				

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS