

Premium Golden Teak Oil Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 11/10/2015 Date of issue: 11/10/2015

#### **SECTION 1: IDENTIFICATION**

**Product Identifier Product Form:** Mixture Product Name: Premium Golden Teak Oil Product Code: 851XX **Intended Use of the Product** Coating.

#### SECTION 2: HAZARDS IDENTIFICATION

<b>Classification of the Substance or</b>	Mixture
Classification (GHS-US)	
Flam. Liq. 4 H227	
Skin Irrit. 2 H315	
Carc. 1B H350	
STOT RE 2 H373	
Asp. Tox. 1 H304	
Label Elements	
GHS-US Labeling	
Hazard Pictograms (GHS-US)	
	CHS07 CHS08
Signal Word (GHS-US)	: Danger
Hazard Statements (GHS-US)	: H227 - Combustible liquid
	H304 - May be fatal if swallowed and enters airways
	H315 - Causes skin irritation
	H336 - May cause drowsiness or dizziness
	H350 - May cause cancer
	H373 - May cause damage to organs through prolonged or repeated exposure
Precautionary Statements (GHS-US)	: P201 - Obtain special instructions before use.
	P202 - Do not handle until all safety precautions have been read and understood.
	P210 - Keep away from heat, sparks, open flames, hot surfaces No smoking.
	P260 - Do not breathe mist, spray, vapors.
	P264 - Wash hands, forearms, and exposed areas thoroughly after handling
	P280 - Wear eye protection, face protection, protective gloves.
	P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER or doctor.
	P302+P352 – IF ON SKIN: Wash with plenty of water.
	P308+P313 - If exposed or concerned: Get medical advice/attention.
	P314 - Get medical advice/attention if you feel unwell.
	P321 - Specific treatment (see Section 4).

P331 - Do NOT induce vomiting.

Version: 2.1

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362 - Take off contaminated clothing and wash before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

#### **Other Hazards**

Aquatic Acute 3 H402 Aquatic Chronic 3 H412

H402 - Harmful to aquatic life

H412 - Harmful to aquatic life with long lasting effects

P273 - Avoid release to the environment.

**Other Hazards:** Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

#### Unknown Acute Toxicity (GHS-US) Not available

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Name	Product identifier	% (w/w)	Classification (GHS-US)
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	40 - 70	Flam. Liq. 4, H227
			Asp. Tox. 1, H304
			Aquatic Acute 2, H401
Distillates, petroleum, hydrotreated middle	(CAS No) 64742-46-7	10 - 24	Acute Tox. 4 (Inhalation:dust,mist), H332
			Skin Irrit. 2, H315
			Carc. 1B, H350
			STOT RE 2, H373
			Asp. Tox. 1, H304
			Aquatic Acute 3, H402
			Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]. A range of concentration as prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

#### **SECTION 4: FIRST AID MEASURES**

#### **Description of First Aid Measures**

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. If vomiting occurs have person lean forward so vomit is not inhaled/aspirated.

#### Most Important Symptoms and Effects Both Acute and Delayed

**General:** Causes skin irritation. May cause cancer. Causes damage to organs. Aspiration hazard. May be fatal if swallowed and enters airways.

Inhalation: May cause respiratory irritation.

Skin Contact: Causes skin irritation.

**Eye Contact:** May cause slight irritation.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Ingestion:** Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury. May be fatal if swallowed and enters airways.

Chronic Symptoms: May cause cancer. May cause damage to organs.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

#### SECTION 5: FIRE-FIGHTING MEASURES

#### **Extinguishing Media**

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>).

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

#### Special Hazards Arising From the Substance or Mixture

Fire Hazard: Combustible liquid.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture.

**Reactivity:** Reacts with strong oxidants causing fire and explosion hazard.

#### **Advice for Firefighters**

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Do not breathe fumes from fires or vapors from decomposition. Use water spray or fog for cooling exposed containers. Do not allow run-off from fire fighting to enter drains or water sources. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products**: Carbon oxides (CO, CO<sub>2</sub>). May liberate toxic gases.

**Reference to Other Sections** 

Refer to section 9 for flammability properties.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### **Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** Use special care to avoid static electric charges. Keep away from open flames, hot surfaces and sources of ignition. No smoking. Avoid breathing (vapor, mist, spray). Use only outdoors or in a well-ventilated area.

#### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Eliminate ignition sources. Stop leak if safe to do so. Ventilate area. **Environmental Precautions** 

#### Prevent entry to sewers and public waters.

#### Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. Contact competent authorities after a spill.

#### **Reference to Other Sections**

See heading 8, Exposure Controls and Personal Protection.

#### **SECTION 7: HANDLING AND STORAGE**

#### Precautions for Safe Handling

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Wash hands and forearms thoroughly after handling.

#### Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Ground/bond container and receiving equipment. Ensure all national/local regulations are observed. **Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep container closed when not in use. Keep in fireproof place. Store locked up. **Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<u>Specific End Use(s)</u> Coatin	g.		
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION			
Control Parameters			
Petroleum distillates, hydrotreated light (64742-47-8)			
British Columbia	OEL TWA (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup> (application restricted to conditions in which	
		there are negligible aerosol exposures)	

#### **Exposure Controls**

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Gas detectors should be used when flammable gases/vapours may be released. Ground/bond container and receiving equipment. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Avoid all unnecessary exposure. Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

**Respiratory Protection:** Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Consumer Exposure Controls: Do not eat, drink, or smoke during use.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Pr	op	erties
Physical State	:	Liquid
Appearance	:	Light brown
Odor	:	Characteristic
Odor Threshold	:	Not available
рН	:	Not available
Evaporation Rate	:	Not available
Melting Point	:	Not available
Freezing Point	:	Not available
Boiling Point	:	149 °C (300.2 °F)
Flash Point	:	65 °C (149 °F)
Auto-ignition Temperature	:	Not available
Decomposition Temperature	:	Not available
Flammability (solid, gas)	:	Not available
Lower Flammable Limit	:	Not available
Upper Flammable Limit	:	Not available
Vapor Pressure	:	Not available
Relative Vapor Density at 20 °C	:	Not available
Specific Gravity/Relative density	:	0.8 mg/mL
Solubility	:	Not soluble in water
Partition coefficient: n-octanol/water	:	Not available
Viscosity	:	Not available
Explosion Data – Sensitivity to Mechanical Impact	:	Not expected to present an explosion hazard due to mechanical impact
Explosion Data – Sensitivity to Static Discharge	:	Not expected to present an explosion hazard due to static discharge

**Safety Data Sheet** 

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Reacts with strong oxidants causing fire and explosion hazard.

**Chemical Stability:** Combustible liquid. May form flammable/explosive vapor-air mixture.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. Aldehydes. Ketones. May release flammable gases.

#### SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified.

**LD50 and LC50 Data:** Not available.

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Not classified.

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not classified.

Carcinogenicity: May cause cancer.

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs through prolonged or repeated exposure.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Causes skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation.

Symptoms/Injuries After Ingestion: Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury. May be fatal if swallowed and enters airways.

Chronic Symptoms: May cause cancer. May cause damage to organs.

#### Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Distillates, petroleum, hydrotreated middle (64742-46-7)		
LD50 Oral Rat	7400 mg/kg	
LD50 Dermal Rabbit	> 2000 mg/kg	
LC50 Inhalation Rat	4.6 mg/l/4h	
ATE US (dust, mist)	4.60 mg/l/4h	
Petroleum distillates, hydrotreated light (64742-47-8)		
LD50 Oral Rat	> 5000 mg/kg	
LD50 Dermal Rabbit	> 2000 mg/kg	
LC50 Inhalation Rat	> 5.2 mg/l/4h	
SECTION 12: ECOLOGICAL INFORMATION		

#### Toxicity

**Ecology** - **General:** Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Distillates, petroleum, hydrotreated middle (64742-46-7)		
LC50 Fish 1	35 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
LC 50 Fish 2	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
Petroleum distillates, hydrotreated light (64742-47-8)		
LC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
LC 50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	
Persistence and Degradability		
Premium Golden Teak Oil		
Persistence and Degradability	Not established.	

# **Premium Golden Teak Oil** Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Bioaccumulative Potential	
Premium Golden Teak Oil	
Bioaccumulative Potential Not establish	hed.
Petroleum distillates, hydrotreated light (64742-47-8)	
BCF fish 1 61 - 159	
Mobility in Soil Not available.	
Other Adverse Effects	
<b>Other Information:</b> Avoid release to the environment.	
SECTION 13: DISPOSAL CONSIDERATIONS	
	material in accordance with all local, regional, national, provincial, territorial
and international regulations.	inacerna in accordance with an iocal, regional, national, provincial, corneral
Additional Information: Handle empty containers with	ı care because residual vapors are flammable.
Ecology – Waste Materials: Hazardous waste due to to	
SECTION 14: TRANSPORT INFORMATION	
In Accordance With ICAO/IATA/DOT/TDG/IMDG	
UN Number	
DOT NA no. : NA1993	
UN Proper Shipping Name	
Proper Shipping Name (DOT)	: COMBUSTIBLE LIQUID, N.O.S. (Contains petroleum distillates hydrotreated
Toher surphing traine (DOT)	light, petroleum distillates hydrotreated middle)
Transport Document Description (DOT)	: NA1993 COMBUSTIBLE LIQUID, N.O.S. (CONTAINS PETROLEUM
masport bocanicit bescription (bo1)	DISTILLATES HYDROTREATED LIGHT, PETROLEUM DISTILLATES
	НУДКОТКЕАТЕД MIDDLE), 3, Ш
Transport Hazard Class(es)	
<b>_</b>	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
DOT Symbols	: D - Proper shipping name for domestic use only, G - Identifies PSN requiring
201091110012	a technical name
Packing Group (DOT)	: Ш - Minor Danger
DOT Special Provisions (49 CFR 172.102)	: B3 - Authorized BCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and
	31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2).
	Additional Requirement: Only liquids with a vapor pressure less than or
	equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at
	131 F) are authorized, except for UN2672 (also see Special Provision IP8 in
	Table 2 for UN2672).
	T1 - 1.5 178.274(d)(2) Normal 178.275(d)(2)
	T4 - 2.65 178.274(d)(2) Normal 178.275(d)(3)
	TP1 - The maximum degree of filling must not exceed the degree of filling
	determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where:
	tr is the maximum mean bulk temperature during transport, and tf is the
	temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 Cfr 173.xxx)	: 150
DOT Packaging Non Bulk (49 Cfr 173.xxx)	: 203
$DOT D_{2} = 1 = -2 = -2 = -2 = -2 = -2 = -2 = -2 $	: 241
DOT Packaging Bulk (49 Cfr 173.xxx)	
Additional Information	. 190
<u>Additional Information</u> Emergency Response Guide (ERG) Number	: 128 • This product mosts the limited quantity exceptions as follows: DOT: Not
<u>Additional Information</u> Emergency Response Guide (ERG) Number	: This product meets the limited quantity exceptions as follows:DOT: Not
<u>Additional Information</u> Emergency Response Guide (ERG) Number	: This product meets the limited quantity exceptions as follows:DOT: Not regulated as dangerous goods except when shipped in bulk. Otherwise, the
Emergency Response Guide (ERG) Number Other Information	: This product meets the limited quantity exceptions as follows:DOT: Not
<u>Additional Information</u> Emergency Response Guide (ERG) Number Other Information <u>Transport by sea</u> Not regulate for transport	: This product meets the limited quantity exceptions as follows:DOT: Not regulated as dangerous goods except when shipped in bulk. Otherwise, the

## **Premium Golden Teak Oil** Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77	, No. 58 / Monday, March 26, 2012 / Rules	and Regulations
Marine Pollutant	: No	
<u>Air transport</u>		
	ssenger Aircraft/Rail (49 CFR 173.	27) : 60 L
	rgo Aircraft Only (49 CFR 175.75)	: 220 L
<b>SECTION 15: REGULATOR</b>	<b>EY INFORMATION</b>	
US Federal Regulations		
Premium Golden Teak Oil		
SARA Section 311/312 Hazar	d Classes	Fire hazard
		Immediate (acute) health hazard
		Delayed (chronic) health hazard
Distillates, petroleum, hydro	treated middle (64742-46-7)	
	SCA (Toxic Substances Control Act	) inventory
Petroleum distillates, hydrot	reated light (64742-47-8)	<u> </u>
× ×	SCA (Toxic Substances Control Act	) inventory
SARA Section 311/312 Hazar	•	Fire hazard
		Immediate (acute) health hazard
US State Regulations		
Distillates, petroleum, hydro	treated middle (64742-46-7)	
U.S Texas - Effects Screenin		
U.S Texas - Effects Screenin	g Levels - Short Term	
Petroleum distillates, hydrot		
	ated Toxic Air Pollutants - Ambien	t Air Levels (AALs) - 24-Hour
	ated Toxic Air Pollutants - Ambien	
U.S Texas - Effects Screenin	g Levels - Long Term	
U.S Texas - Effects Screenin	g Levels - Short Term	
Canadian Regulations		
Premium Golden Teak Oil		
WHMIS Classification	Class B Division 3 - Combustible	Liquid
	Class D Division 2 Subdivision A	- Very toxic material causing other toxic effects
	Class D Division 2 Subdivision B	- Toxic material causing other toxic effects
	Ţ	
Distillates, petroleum, hydro	treated middle (64742-46-7)	
¥	Oomestic Substances List) inventor	у.
WHMIS Classification		- Very toxic material causing other toxic effects
		- Toxic material causing other toxic effects
Petroleum distillates, hydrot	reated light (64742-47-8)	
×	Oomestic Substances List) inventor	ν.
WHMIS Classification	Class B Division 3 - Combustible	
		- Toxic material causing other toxic effects
This product has been classifi		criteria of the Controlled Products Regulations (CPR) and the SDS
contains all of the information	n required by CPR.	
SECTION 16: OTHER INFO	RMATION, INCLUDING DAT	E OF PREPARATION OR LAST REVISION
Revision date	: 11/10/2015	
Other Information		n prepared in accordance with the SDS requirements of the OSHA
		on Standard 29 CFR 1910.1200.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **GHS Full Text Phrases:**

Acute Tox. 4	Acute toxicity (inhalation:dust,mist) Category 4
(Inhalation:dust,mist)	
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H332	Harmful if inhaled
H350	May cause cancer
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
PA Health Hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt
PA Fire Hazard	<ul> <li>medical attention is given.</li> <li>2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.</li> </ul>
PA Reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2