



## TECHNICAL DATA SHEET

### SUPER LUBE® SPORTSMAN'S KIT

#### PRODUCT DESCRIPTION:

Super Lube® Sportsman's Kit\*

This lubricant kit contains the following components:

1 – 7 ml Precision Oiler (P/N 51014)

1 – ½ oz. tube Super Lube® Multi-Purpose Synthetic Grease with Synconol® (PTFE) (21014)

1 – Cleaning cloth

3 – Foam tip swabs

\*Comes packaged in a handy clear plastic container



Super Lube® Multi-Purpose Synthetic Oil is a premium synthetic oil with suspended Synconol® (PTFE) particles that is used as a general-purpose lubricant. It provides protection against friction, wear, rust and corrosion and is safe to use on metal, plastic, wood, leather, painted surfaces and most rubbers.

Super Lube® Grease is a patented synthetic NLGI grade 2, heavy-duty, multi-purpose lubricant with Synconol® (PTFE). Synthetic base fluids and the addition of Synconol® (PTFE) micro powders combine to form a premium lubricant that provides longer life protection against friction, wear, rust and corrosion. Super Lube® Grease offers good mechanical stability, does not evaporate or form gummy deposits. It will not melt or separate.

Super Lube® Multi-Purpose Synthetic Oil with Synconol® (PTFE) and Super Lube® Grease are NSF Food Grade rated H1 and are safe for incidental food contact. Both meet former USDA (H1) guidelines.

#### FEATURES:

- ❖ Easy to use 7 ml Precision Oiler with our Synconol® (PTFE) fortified oil
- ❖ ½ oz. tube of our Multi-Purpose synthetic grease with built in precision nozzle
- ❖ Dielectric
- ❖ Food Grade, clean
- ❖ Kosher
- ❖ Environmentally friendly
- ❖ NSF Registered (H1), # 096790 (grease) and # 136742 (oil)

#### TYPICAL APPLICATIONS:

- ❖ Firearms
- ❖ Fishing reels
- ❖ Hunting gear
- ❖ O-rings
- ❖ Flashlights
- ❖ Battery terminals
- ❖ Motorcycles
- ❖ Bicycles
- ❖ Roller skates
- ❖ Boating
- ❖ Cross bows (rail lubricant)
- ❖ Compound bows



TECHNICAL DATA SHEET  
SUPER LUBE® SPORTSMAN’S KIT

PACKAGE SIZES:

Part No.	Description
11520	Sportsman’s Kit

PROPERTIES:

Super Lube® Multi-Purpose Synthetic Oil with Syncon® (PTFE)

Test	Test Method	Rating
Color:		Translucent clear
Temperature range:		-45°F to 450°F (-43°C to 232°C)
ISO Viscosity grade:	ASTM D445	150 cSt
Viscosity Index:	ASTM D2270	145
Specific gravity:	ASTM D1298	.89
Timken OK Load:	ASTM D2782	40 lbs

Super Lube® Multi-Purpose Synthetic Grease with Syncon® (PTFE)

Test	Test Method	Rating
Color:		Translucent White
NLGI Grade:	ASTM D217	2
Dropping Point:	ASTM D2265	>550°F (287°C)
Four Ball Wear	ASTM D2266	<1.0 mm
Load wear index:	ASTM 2596	70.63 kgf
Weld point:		400 kg
Oxidation Stability - 100 hrs.	ASTM D942	0.5 psi drop
Wheel bearing leakage:	ASTM D1263	< 1.0 g
Copper Corrosion - 24 hrs. @ 100°C	ASTM D4048	1B, shiny
Water Washout:	ASTM 1264	< 1%

DIRECTIONS:

- Clean and dry area to be treated.
- Apply lubricant until the area is completely covered.
- Re-apply as necessary.

Learn more about boat maintenance and winterization we have.