

Description

High Strength, Forged, Hot Dipped Galvanized Shackles

- Breaking strength exceeds that of high test G4 chain
- 30% stronger than standard Grade A shackles (depending on sizes)
- Forged, Hot Dip Galvanized coating on both the shackle and pin
- Working load limit, size, and logo stamped on every shackle
- Bold black colored pin
- Proof tested & load rated
- Bow (Anchor) and D (Chain) types

PART ID	SIZE				WORKING LOAD LIMIT			BREAKING LOAD			
	BAIL		PIN		kn	lb	kg	kn	lb	kg	
	in	mm	in	mm							
Anchor Type	10321196	5/16	8	3/8	10	11	2500	1135	57	12500	5675
	10319610	3/8	10	7/16	11	18	4000	1816	91	20000	9080
	10319611	7/16	11	1/2	13	24	5200	2361	118	26000	11804
	10319612	1/2	13	5/8	16	30	6600	2996	150	33000	14982
	10319613	5/8	16	3/4	19	45	10000	4540	227	50000	22700
	10319614	3/4	19	7/8	22	64	14000	6356	318	70000	31780
	10319615	7/8	22	1	25	86	19000	8626	431	95000	43130
	10319616	1	25	1 1/8	29	114	25000	11350	568	125000	56750
	10319617	1 1/8	29	1 1/4	32	136	30000	13620	681	150000	68100
	10319618	1 1/4	32	1 3/8	35	163	36000	16344	817	180000	81720
10319619	1 3/8	35	1 1/2	38	191	42000	19068	953	210000	95340	
Chain Type	10321197	5/16	8	3/8	10	11	2500	1135	57	12500	5675
	10319620	3/8	10	7/16	11	18	4000	1816	91	20000	9080
	10319621	7/16	11	1/2	13	24	5200	2361	118	26000	11804
	10319622	1/2	13	5/8	16	30	6600	2996	150	33000	14982
	10319623	5/8	16	3/4	19	45	10000	4540	227	50000	22700
	10319624	3/4	19	7/8	22	64	14000	6356	318	70000	31780
	10319625	7/8	22	1	25	86	19000	8626	431	95000	43130
	10319626	1	25	1 1/8	29	114	25000	11350	568	125000	56570
	10319627	1 1/8	29	1 1/4	32	136	30000	13620	681	150000	68100
	10319628	1 1/4	32	1 3/8	35	163	36000	16344	817	180000	81720
10319629	1 3/8	35	1 1/2	38	191	42000	19068	953	210000	95340	