




TRIDENT MARINE®

HD & XHD WATER HOSE (SAE J20R3)



134 Series

Trident Cost effective, Hi Temp, EPDM rubber, polyester reinforced and exceeds SAE J20R3. Both are resistant to coolants, ozone, cold & heat; and serve a variety of boat and plant pressurized applications (water & air delivery).

Specifications

Construction:

Tube & Cover:
EDPM Rubber

Color: Black

Reinforcement:
Polyester reinforcement

Temperature Range:
-40F-212°F (-40°C-100°C)

Coils:
700' (213.4m)

Boxed :
50' (15.24m)

Part Number	ID		OD		Working Pressure		Weight		Bend Radius	
	in.	mm.	in.	mm.	Psi	Bar	Lb./50 ft.	Kg/m	in	mm
134-0140	1/4	6.4	.5	12.7	300	20.7	4.5	0.13	.75	19.1
134-0560	5/6	7.9	.594	15.1	300	20.7	6	0.18	1.37	34.9
134-0380	3/8	9.5	.656	16.7	300	20.7	7	0.21	1.25	31.8
134-0120	1/2	12.7	.813	20.7	300	20.7	10	0.30	2	50.8
134-0580	5/8	15.9	.969	24.6	300	20.7	12	0.36	2.5	63.5
134-0340	3/4	19.1	1.062	27	300	20.7	18	0.52	3.27	83.2
134-1000	1	25.4	1.406	35.7	300	20.7	22	0.66	4.37	111

*Burst Pressure is 4 x Working Pressure

TRIDENT RUBBER INC.

Rely on premium boat pumps & plumbing by Trident if you're looking for quality and efficiency.