



TRIDENT MARINE®

260 Series Connector Tubes



260 Series

Our fibreglass connectors are a corrosion resistant high temperature exhaust tube designed specifically to minimize exhaust gas and cooling water flow restrictions on wet exhaust systems. Precise outside diameters facilitate perfect connections between sections of tubing and flexible elbows, bellows or hoses. Meets UL94V-0 for flame retardancy.

Specifications

Construction:

Resin: Class 1 Fire Retardant Epoxy Vinyl Ester Thermoset

Glass: Corrosion Resistant E Glass

Color: Amber

Reinforcement: Filament Winding

Temperature Range: up to 350°F (177°C)

Trident Part No.	OD +/- 0.030		Length	
	Inches	mm	Inches	mm
260-2001	2	50.8	4	101.6
260-2120	2.5	63.5	4	101.6
260-3001	3	76.2	4	101.6
260-3121	3.5	89	4	101.6
260-4001	4	101.6	6	152.4
260-4121	4.5	114.3	6	152.4
260-5001	5	127	6	152.4
260-6001	6	152.4	6	152.4
260-8001	8	203.2	8	203.2
260-10001	10	254	12	304.8
260-12001	12	304.8	12	304.8
260-14001	14	355.6	14	355.6
260-16001	16	406.4	16	406.4
260-18001	18	457.2	18	457.2